

# 3-27x56 PM II High Power - 3-27x56 PM II High Power LP TREMOR3 1cm ccw DT35 MTC LT / ST ZC CT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-27×56 PM II High Power from Schmidt and Bender is a premier tactical riflescope engineered for ultimate versatility—capable of precise performance from near-range engagements all the way to extreme long-distance targets. With an expansive 3-27× magnification range, this scope adapts effortlessly across calibres and mission profiles.

Its 56 mm objective lens offers exceptional light gathering and clarity, enabling detailed target acquisition even at great distances. The field of view spans approximately 13.0–1.4 m at 100 m, while the exit pupil ranges around 8.7–2.1 mm. Generous eye relief of around 90 mm ensures comfortable alignment and a stable sight picture.

Built on a rugged 34 mm main tube, the scope is constructed for demanding environments. The turret system accommodates ultra-fine click values (e.g., ~0.1 mrad) and massive internal adjustment ranges for elevation and windage—making it suitable for long-range engagement scenarios. Parallax adjustment commonly spans from around 10 m to infinity, giving flexibility across varied target distances.

Key Specifications:

Magnification: 3-27×

Objective Lens Diameter: 56 mm

Main Tube Diameter: 34 mm

Field of View: approx. 13.0-1.4 m @100 m

Exit Pupil: approx. 8.7-2.1 mm

Eye Relief: approx. 90 mm

Click Value: approx. 0.1 mrad (~0.5 cm @100 m) depending on configuration

Parallax: from ~10 m to infinity

Crafted with German precision, the 3-27×56 PM II High Power is ideal for professionals, competition marksmen or hunters who demand the highest optical clarity, mechanical resilience and full versatility across a wide range of engagement distances.

## Attributes

- Name: [3-27x56 PM II High Power LP TREMOR3 1cm ccw DT35 MTC LT / ST ZC CT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015953
- Mfr. No.: 669-911-532-F1-E8
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537064865

NO IMAGE  
AVAILABLE

# Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for 3-27x56 PM II High Power](#)
- [About Us](#)

# Safety Instruction Guide for 3-27x56 PM II High Power

## Introduction

Thank you for choosing the 3-27x56 PM II High Power riflescope from Schmidt and Bender. This guide provides essential safety instructions to ensure safe and effective use of your product. Please read this document carefully before using the scope to understand the potential hazards and how to avoid them.

## General Safety Guidelines

- Ensure safe use of the riflescope by following all instructions provided in this guide.
- Always handle the riflescope with care to prevent damage or injury.
- Be aware of your surroundings and ensure a safe environment when using the riflescope.
- Store the riflescope in a secure location, out of reach of children and vulnerable individuals.
- Regularly check for any updates regarding product recalls or safety information on the EU Safety Gate platform.

## Specific Safety Precautions for Use

- Do not look directly at the sun through the riflescope, as this can cause severe eye damage.
- Ensure that the riflescope is securely mounted to your firearm before use to prevent accidents.
- Use the riflescope only for its intended purpose—longrange shooting and target acquisition.
- Always keep the riflescope clean and free of obstructions to ensure optimal performance.
- Avoid using the riflescope in extreme weather conditions that may affect its functionality, such as heavy rain or snow.
- Be cautious when adjusting the turrets and parallax settings to avoid unintended shots.

## Instructions for Installation and Usage

### Installation

- Before installation, ensure that your firearm is unloaded and pointed in a safe direction.
- Use the provided mounting rings to securely attach the riflescope to the firearm's rail system.
- Align the riflescope so that it is level with the barrel of the firearm.
- Tighten the mounting screws evenly to avoid any misalignment.

### Usage

- Adjust the magnification by rotating the magnification ring to your desired level (3-27x).
- Focus the reticle using the diopter adjustment ring until the reticle appears sharp.
- Adjust the elevation and windage turrets to zero in your scope according to your shooting requirements.
- Use the parallax adjustment to ensure a clear image at your target distance.
- Always check your surroundings and ensure a safe shooting environment before taking a shot.

## Disposal Instructions

- Dispose of the riflescope in accordance with local regulations regarding electronic waste and optical products.
- Do not dispose of the riflescope in regular household waste.
- Contact your local waste management authority for information on proper disposal methods.

## **Contact Information for Further Support**

For any inquiries or support regarding the 3-27x56 PM II High Power riflescope, please refer to the product packaging for the EUbased contact information.

## **Conclusion**

By following these safety instructions, you can ensure a safe and enjoyable experience with your 3-27x56 PM II High Power riflescope. Always prioritize safety and remain informed about any updates or recalls related to your product. Thank you for your attention to these important safety guidelines.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)