

3-27x56 PM II High Power - 3-27x56 PM II High Power LP MSR2 1cm ccw DT II+ MTC LT / ST II ZC LT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-27x56 PM II High Power from Schmidt and Bender is a premier tactical riflescope engineered for ultimate versatility—capable of precise performance from near-range engagements all the way to extreme long-distance targets. With an expansive 3-27x magnification range, this scope adapts effortlessly across calibres and mission profiles.

Its 56 mm objective lens offers exceptional light gathering and clarity, enabling detailed target acquisition even at great distances. The field of view spans approximately 13.0-1.4 m at 100 m, while the exit pupil ranges around 8.7-2.1 mm. Generous eye relief of around 90 mm ensures comfortable alignment and a stable sight picture.

Built on a rugged 34 mm main tube, the scope is constructed for demanding environments. The turret system accommodates ultra-fine click values (e.g., ~0.1 mrad) and massive internal adjustment ranges for elevation and windage—making it suitable for long-range engagement scenarios. Parallax adjustment commonly spans from around 10 m to infinity, giving flexibility across varied target distances.

Key Specifications:

Magnification: 3-27x

Objective Lens Diameter: 56 mm

Main Tube Diameter: 34 mm

Field of View: approx. 13.0-1.4 m @100 m

Exit Pupil: approx. 8.7-2.1 mm

Eye Relief: approx. 90 mm

Click Value: approx. 0.1 mrad (~0.5 cm @100 m) depending on configuration

Parallax: from ~10 m to infinity

Crafted with German precision, the 3-27x56 PM II High Power is ideal for professionals, competition marksmen or hunters who demand the highest optical clarity, mechanical resilience and full versatility across a wide range of engagement distances.

Attributes

- Name: [3-27x56 PM II High Power LP MSR2 1cm ccw DT II+ MTC LT / ST II ZC LT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015955
- Mfr. No.: 669-911-842-M2-I5
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537043259

NO IMAGE
AVAILABLE

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for 3-27x56 PM II High Power](#)
- [About Us](#)

Safety Instruction Guide for 3-27x56 PM II High Power

Introduction

Thank you for choosing the 3-27x56 PM II High Power riflescope from Schmidt and Bender. This guide provides essential safety instructions to ensure the safe and effective use of your product. Please read this guide thoroughly before using the riflescope.

General Safety Guidelines

- **Product Safety:** This riflescope is designed for safe use. Always handle it with care to avoid accidents.
- **Enhanced Recalls:** In the unlikely event of a product recall, you will be notified through standardized notices. Follow the instructions provided for returns and remedies.
- **Online Shopping:** If purchased online, ensure that the retailer complies with safety requirements equivalent to those of physical stores.
- **Special Consumer Focus:** This product is not intended for use by children. Keep it out of reach of minors.
- **EU Contact Point:** For any safety inquiries, please refer to the EU contact point provided by your retailer.
- **Rapid Alerts:** Stay informed about product safety updates by checking the EU's Safety Gate platform regularly.

Specific Safety Precautions for Use

- **Proper Handling:** Always handle the riflescope with clean hands. Avoid touching the lenses with fingers or other objects to prevent scratches.
- **Secure Mounting:** Ensure that the riflescope is securely mounted on the firearm. Follow the mounting instructions carefully to prevent it from coming loose during use.
- **Avoid Excessive Force:** Do not apply excessive force when adjusting the turrets or mounting the scope. This can cause damage.
- **Use Appropriate Ammunition:** Only use ammunition that is compatible with your firearm and the intended use of the riflescope.
- **Environmental Considerations:** Avoid exposing the riflescope to extreme temperatures, moisture, or direct sunlight for extended periods.
- **Regular Inspections:** Periodically check the riflescope for any signs of wear or damage. If any issues are detected, cease use immediately and consult a professional.

Instructions for Installation and Usage

1. Installation:

- Select a suitable mounting base for your firearm.
- Securely attach the riflescope to the mounting base using the appropriate screws and tools.
- Ensure the riflescope is level and aligned with the firearm before tightening the screws completely.

2. Adjustment:

- Familiarize yourself with the turret system for elevation and windage adjustments.
- Make adjustments in small increments to ensure accuracy.

3. Using the Riflescope:

- Adjust the magnification according to your target distance.
- Use the parallax adjustment feature to enhance clarity based on the distance of the target.
- Maintain a stable shooting position to ensure a clear sight picture.

4. **PostUse Care:**

- After use, clean the lenses with a soft, lintfree cloth. Do not use harsh chemicals or abrasive materials.
- Store the riflescope in a protective case to prevent damage.

Disposal Instructions

- **Environmental Responsibility:** Dispose of the riflescope and any associated components in accordance with local regulations.
- **Electronic Waste:** If applicable, take the product to an authorized electronic waste recycling facility.

Contact Information for Further Support

For any questions or concerns regarding the use or safety of your 3-27x56 PM II High Power riflescope, please consult the retailer from whom you purchased the product for assistance.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk