

3-27x56 PM II High Power - 3-27x56 PM II High Power LP P4FL 0,05 mrad ccw MT II MTC LT / DT II+ ZC LT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-27×56 PM II High Power from Schmidt and Bender is a premier tactical riflescope engineered for ultimate versatility—capable of precise performance from near-range engagements all the way to extreme long-distance targets. With an expansive 3-27× magnification range, this scope adapts effortlessly across calibres and mission profiles.

Its 56 mm objective lens offers exceptional light gathering and clarity, enabling detailed target acquisition even at great distances. The field of view spans approximately 13.0–1.4 m at 100 m, while the exit pupil ranges around 8.7–2.1 mm. Generous eye relief of around 90 mm ensures comfortable alignment and a stable sight picture.

Built on a rugged 34 mm main tube, the scope is constructed for demanding environments. The turret system accommodates ultra-fine click values (e.g., ~0.1 mrad) and massive internal adjustment ranges for elevation and windage—making it suitable for long-range engagement scenarios. Parallax adjustment commonly spans from around 10 m to infinity, giving flexibility across varied target distances.

Key Specifications:

Magnification: 3-27×

Objective Lens Diameter: 56 mm

Main Tube Diameter: 34 mm

Field of View: approx. 13.0-1.4 m @100 m

Exit Pupil: approx. 8.7-2.1 mm

Eye Relief: approx. 90 mm

Click Value: approx. 0.1 mrad (~0.5 cm @100 m) depending on configuration

Parallax: from ~10 m to infinity

Crafted with German precision, the 3-27×56 PM II High Power is ideal for professionals, competition marksmen or hunters who demand the highest optical clarity, mechanical resilience and full versatility across a wide range of engagement distances.

Attributes

- Name: [3-27x56 PM II High Power LP P4FL 0,05 mrad ccw MT II MTC LT / DT II+ ZC LT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015958
- Mfr. No.: 669-911-972-I5-H5
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537026795

NO IMAGE
AVAILABLE

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 3-27x56 PM II High Power Riflescope](#)
- [About Us](#)

Safety Instruction Guide for the 3-27x56 PM II High Power Riflescope

Introduction

Thank you for choosing the 3-27x56 PM II High Power Riflescope from Schmidt and Bender. This guide provides essential safety instructions to ensure the safe use, installation, and disposal of your riflescope. It is important to follow these guidelines to maximize your safety and the performance of the product.

General Safety Guidelines

- Always handle the riflescope with care. Avoid dropping or subjecting it to strong impacts.
- Use the riflescope only for its intended purpose. Do not modify or alter the product.
- Keep the riflescope out of reach of children and unauthorized users.
- Ensure that the riflescope is securely mounted on your firearm before use.
- Regularly inspect the riflescope for any signs of damage or wear. Do not use if damaged.
- Follow all local laws and regulations regarding the use of firearms and riflescopes.

Specific Safety Precautions for Use

- **Eye Protection:** Always wear appropriate eye protection when using the riflescope to prevent injury from recoil or debris.
- **Environmental Conditions:** Avoid using the riflescope in extreme weather conditions (e.g., heavy rain, snow, or extreme heat) that may affect its performance.
- **Shooting Range Safety:** Follow all safety protocols at shooting ranges, including keeping the muzzle pointed in a safe direction and being aware of your surroundings.
- **Target Identification:** Always positively identify your target before firing. Never shoot at movement or sounds without confirmation.
- **Handling Ammunition:** Store ammunition safely and out of reach of children. Use only the recommended calibre for your riflescope.

Instructions for Installation and Usage

1. Mounting the Riflescope:

- Select a suitable mounting base compatible with your rifle.
- Securely attach the mounting rings to the base.
- Place the riflescope in the rings and tighten the screws evenly to avoid misalignment.
- Ensure the riflescope is level and aligned with the rifle's barrel.

2. Adjusting the Turrets:

- Familiarize yourself with the turret system for elevation and windage adjustments.
- Make adjustments gradually and check your zeroing after each change.

3. Focusing the Reticle:

- Adjust the eyepiece until the reticle appears sharp and clear.
- Test the focus at different distances to ensure clarity.

4. Parallax Adjustment:

- Adjust the parallax setting according to the distance of your target for improved accuracy.

- Ensure the parallax is set correctly to avoid aiming errors.

5. Using the Magnification:

- Rotate the magnification ring to select the desired level of zoom.
- Practice at various distances to become familiar with the scope's capabilities.

Disposal Instructions

- Dispose of the riflescope in accordance with local regulations.
- Do not dispose of the product in regular household waste.
- If the product is damaged or no longer functional, consider recycling components where possible.

Contact Information for Further Support

For any questions or concerns regarding the safety and use of your 3-27x56 PM II High Power Riflescope, please refer to the manufacturer's contact information provided with the product.

By following these safety instructions, you can ensure a safe and enjoyable experience with your riflescope. Always prioritize safety and responsible firearm use.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk