

3-27x56 PM II High Power - 3-27x56 PM II High Power LP MSR2 0,05 mrad ccw MT II MTC LT / DT II+ ZC LT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-27x56 PM II High Power from Schmidt and Bender is a premier tactical riflescope engineered for ultimate versatility—capable of precise performance from near-range engagements all the way to extreme long-distance targets. With an expansive 3-27x magnification range, this scope adapts effortlessly across calibres and mission profiles.

Its 56 mm objective lens offers exceptional light gathering and clarity, enabling detailed target acquisition even at great distances. The field of view spans approximately 13.0-1.4 m at 100 m, while the exit pupil ranges around 8.7-2.1 mm. Generous eye relief of around 90 mm ensures comfortable alignment and a stable sight picture.

Built on a rugged 34 mm main tube, the scope is constructed for demanding environments. The turret system accommodates ultra-fine click values (e.g., ~0.1 mrad) and massive internal adjustment ranges for elevation and windage—making it suitable for long-range engagement scenarios. Parallax adjustment commonly spans from around 10 m to infinity, giving flexibility across varied target distances.

Key Specifications:

Magnification: 3-27x

Objective Lens Diameter: 56 mm

Main Tube Diameter: 34 mm

Field of View: approx. 13.0-1.4 m @100 m

Exit Pupil: approx. 8.7-2.1 mm

Eye Relief: approx. 90 mm

Click Value: approx. 0.1 mrad (~0.5 cm @100 m) depending on configuration

Parallax: from ~10 m to infinity

Crafted with German precision, the 3-27x56 PM II High Power is ideal for professionals, competition marksmen or hunters who demand the highest optical clarity, mechanical resilience and full versatility across a wide range of engagement distances.

Attributes

- Name: [3-27x56 PM II High Power LP MSR2 0,05 mrad ccw MT II MTC LT / DT II+ ZC LT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015959
- Mfr. No.: 669-911-842-I5-H5
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537026832

NO IMAGE
AVAILABLE

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 3-27x56 PM II High Power Riflescope](#)
- [About Us](#)

Safety Instruction Guide for the 3-27x56 PM II High Power Riflescope

Introduction

Thank you for choosing the 3-27x56 PM II High Power Riflescope by Schmidt and Bender. This guide provides essential safety information and instructions to ensure the safe and effective use of your new riflescope. Please read this guide carefully before use.

General Safety Guidelines

- **Product Safety:** This riflescope is designed for safe use in various conditions. Ensure you follow all safety guidelines to minimize risks.
- **Enhanced Recalls:** In the event of a product recall, standardized notices will be provided. Please stay informed about recalls and follow the instructions given.
- **Online Shopping Safety:** When purchasing online, ensure that the retailer complies with safety regulations similar to physical stores.
- **Special Consumer Focus:** Extra precautions should be taken to protect vulnerable groups, including children. Keep the product out of reach of children.
- **EU Contact Point:** For any safety inquiries, please refer to the EU contact point provided by the manufacturer.
- **Rapid Alerts:** Stay updated on any unsafe product alerts through the EU Safety Gate platform.

Specific Safety Precautions for Use

- **Proper Handling:** Always handle the riflescope with care. Avoid dropping or subjecting it to strong impacts.
- **Avoid Moisture:** Protect the riflescope from excessive moisture and humidity. Store it in a dry place.
- **Temperature Extremes:** Do not expose the riflescope to extreme temperatures, as this may affect its performance.
- **Cleaning:** Use only a soft, dry cloth to clean the lenses. Avoid using harsh chemicals or abrasive materials.
- **Mounting:** Ensure the riflescope is securely mounted to the rifle before use. Follow the manufacturer's instructions for mounting.
- **Eye Protection:** Always use appropriate eye protection when using firearms equipped with this riflescope.

Instructions for Installation and Usage

1. Installation:

- Choose a suitable mounting location on your rifle.
- Follow the manufacturer's instructions for attaching the riflescope securely.
- Ensure that the riflescope is aligned properly for optimal accuracy.

2. Usage:

- Adjust the magnification as needed for your shooting distance.
- Use the turret system to make precise adjustments for elevation and windage.
- Regularly check the focus and parallax settings to ensure clear sighting.
- Maintain a stable shooting position to avoid unnecessary movement.

Disposal Instructions

- **Environmental Responsibility:** Dispose of the riflescope in accordance with local regulations. Do not dispose of it in general waste.
- **Recycling:** If applicable, recycle components of the riflescope according to local recycling guidelines.

Contact Information for Further Support

For any additional support or safety inquiries, please refer to the manufacturer's official website or contact the designated EU contact point.

Thank you for your attention to these safety instructions. Enjoy your experience with the 3-27x56 PM II High Power Riflescope, and always prioritize safety in your shooting activities.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk