

# 3-27x56 PM II High Power - 3-27x56 PM II High Power LP P4FL 1cm cw DT27 MTC LT / ST ZC CT RAL 8000

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-27×56 PM II High Power from Schmidt and Bender is a premier tactical riflescope engineered for ultimate versatility—capable of precise performance from near-range engagements all the way to extreme long-distance targets. With an expansive 3-27× magnification range, this scope adapts effortlessly across calibres and mission profiles.

Its 56 mm objective lens offers exceptional light gathering and clarity, enabling detailed target acquisition even at great distances. The field of view spans approximately 13.0–1.4 m at 100 m, while the exit pupil ranges around 8.7–2.1 mm. Generous eye relief of around 90 mm ensures comfortable alignment and a stable sight picture.

Built on a rugged 34 mm main tube, the scope is constructed for demanding environments. The turret system accommodates ultra-fine click values (e.g., ~0.1 mrad) and massive internal adjustment ranges for elevation and windage—making it suitable for long-range engagement scenarios. Parallax adjustment commonly spans from around 10 m to infinity, giving flexibility across varied target distances.

Key Specifications:

Magnification: 3-27×

Objective Lens Diameter: 56 mm

Main Tube Diameter: 34 mm

Field of View: approx. 13.0-1.4 m @100 m

Exit Pupil: approx. 8.7-2.1 mm

Eye Relief: approx. 90 mm

Click Value: approx. 0.1 mrad (~0.5 cm @100 m) depending on configuration

Parallax: from ~10 m to infinity

Crafted with German precision, the 3-27×56 PM II High Power is ideal for professionals, competition marksmen or hunters who demand the highest optical clarity, mechanical resilience and full versatility across a wide range of engagement distances.

## Attributes

- Name: [3-27x56 PM II High Power LP P4FL 1cm cw DT27 MTC LT / ST ZC CT RAL 8000](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015960
- Mfr. No.: 669-945-972-G9-E9
- Colour: FDE
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537065022

NO IMAGE  
AVAILABLE

# Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for 3-27x56 PM II High Power](#)
- [About Us](#)

# Safety Instruction Guide for 3-27x56 PM II High Power

## Introduction

Thank you for choosing the 3-27x56 PM II High Power from Schmidt and Bender. This tactical riflescope is designed for versatility and high performance in various shooting scenarios. To ensure your safety and the effective use of this product, please read and follow the safety instructions outlined in this guide.

## General Safety Guidelines

- Always handle the riflescope with care and ensure it is securely mounted on the firearm.
- Keep the riflescope out of reach of children and unauthorized users.
- Inspect the riflescope regularly for any signs of damage or wear.
- Use the riflescope only for its intended purpose.
- Follow all local laws and regulations regarding the use of firearms and optics.
- Report any unsafe products or incidents to the appropriate authorities.

## Specific Safety Precautions for Use

- **Eye Protection:** Always wear appropriate eye protection when using the riflescope.
- **Firearm Safety:** Treat every firearm as if it is loaded. Ensure the firearm is pointed in a safe direction at all times.
- **Environmental Awareness:** Be aware of your surroundings and ensure that there are no people or animals in the line of fire.
- **Proper Adjustment:** Make sure to adjust the turrets and parallax settings carefully to avoid miscalculations during shooting.
- **Weather Considerations:** Avoid using the riflescope in extreme weather conditions that may affect visibility or performance.

## Instructions for Installation and Usage

### 1. Installation:

- Ensure that the firearm is unloaded and pointed in a safe direction.
- Mount the riflescope securely on the main tube (34 mm) using the appropriate rings and base.
- Align the reticle with the bore of the firearm for accurate aiming.

### 2. Usage:

- Adjust the magnification from 3x to 27x as needed for your shooting distance.
- Use the objective lens (56 mm) to gather light for optimal clarity.
- Set the parallax adjustment according to the distance of the target, typically from 10 m to infinity.
- Check and adjust the eye relief (approximately 90 mm) for a comfortable viewing experience.
- Utilize the click values for elevation and windage adjustments (approximately 0.1 mrad) to ensure precision.

## Disposal Instructions

- Dispose of the riflescope responsibly and in accordance with local regulations.
- Do not dispose of the product in household waste.
- Consider recycling options for the materials used in the riflescope.

## **Contact Information for Further Support**

For any safety inquiries or additional support, please refer to the manufacturer's contact information provided in the product packaging or visit the official website.

By following these guidelines, you can ensure a safe and effective experience with your 3-27x56 PM II High Power riflescope. Thank you for your attention to these important safety instructions.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)