

3-27x56 PM II High Power - 3-27x56 PM II High Power LP MSR2 1cm cw DT27 MTC LT / ST ZC CT RAL 8000

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-27×56 PM II High Power from Schmidt and Bender is a premier tactical riflescope engineered for ultimate versatility—capable of precise performance from near-range engagements all the way to extreme long-distance targets. With an expansive 3-27× magnification range, this scope adapts effortlessly across calibres and mission profiles.

Its 56 mm objective lens offers exceptional light gathering and clarity, enabling detailed target acquisition even at great distances. The field of view spans approximately 13.0–1.4 m at 100 m, while the exit pupil ranges around 8.7–2.1 mm. Generous eye relief of around 90 mm ensures comfortable alignment and a stable sight picture.

Built on a rugged 34 mm main tube, the scope is constructed for demanding environments. The turret system accommodates ultra-fine click values (e.g., ~0.1 mrad) and massive internal adjustment ranges for elevation and windage—making it suitable for long-range engagement scenarios. Parallax adjustment commonly spans from around 10 m to infinity, giving flexibility across varied target distances.

Key Specifications:

Magnification: 3-27×

Objective Lens Diameter: 56 mm

Main Tube Diameter: 34 mm

Field of View: approx. 13.0-1.4 m @100 m

Exit Pupil: approx. 8.7-2.1 mm

Eye Relief: approx. 90 mm

Click Value: approx. 0.1 mrad (~0.5 cm @100 m) depending on configuration

Parallax: from ~10 m to infinity

Crafted with German precision, the 3-27×56 PM II High Power is ideal for professionals, competition marksmen or hunters who demand the highest optical clarity, mechanical resilience and full versatility across a wide range of engagement distances.

Attributes

- Name: [3-27x56 PM II High Power LP MSR2 1cm cw DT27 MTC LT / ST ZC CT RAL 8000](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015961
- Mfr. No.: 669-945-842-G9-E9
- Colour: FDE
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537065053

NO IMAGE
AVAILABLE

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for 3-27x56 PM II High Power](#)
- [About Us](#)

Safety Instruction Guide for 3-27x56 PM II High Power

Introduction

Thank you for choosing the 3-27x56 PM II High Power riflescope from Schmidt and Bender. This guide provides essential safety instructions and guidelines to ensure the safe and effective use of your product. Please read this document carefully and keep it for future reference.

General Safety Guidelines

- Ensure that all users are familiar with the operation and safety features of the riflescope.
- Always handle the riflescope with care to avoid damage or injury.
- Store the riflescope in a safe and secure place when not in use, away from children and unauthorized users.
- Regularly inspect the riflescope for any signs of damage or wear before each use.
- Follow all local laws and regulations regarding the use of firearms and optics.
- If you notice any unusual behavior or performance issues with the riflescope, cease use immediately and consult a professional.

Specific Safety Precautions for Use

- Always use the riflescope in a safe and controlled environment.
- Never point the riflescope at anything you do not intend to shoot.
- Ensure that the riflescope is properly mounted and securely attached to the firearm before use.
- Use appropriate eye protection while using the riflescope.
- Be aware of your surroundings and ensure that there are no people or animals in the line of fire.
- Avoid using the riflescope in adverse weather conditions that may impair visibility or safety.
- Do not attempt to modify or disassemble the riflescope, as this may void the warranty and pose safety risks.

Instructions for Installation and Usage

1. Installation

- Ensure you have the necessary tools for mounting the riflescope.
- Select a suitable mounting location on your firearm, ensuring it is compatible with the 34 mm main tube diameter.
- Securely attach the riflescope to the firearm using the appropriate mounting rings or bases.
- Check that the riflescope is level and properly aligned with the barrel of the firearm.
- Tighten all screws and mounts to the manufacturer's specifications.

2. Usage

- Adjust the magnification using the zoom ring according to your target distance.
- Use the turret system to make precise adjustments for elevation and windage.
- Adjust the parallax setting to match the distance of your target for optimal clarity.
- Maintain a comfortable eye relief of approximately 90 mm while aiming through the riflescope.
- Always check the field of view and exit pupil before taking your shot.

Disposal Instructions

- Dispose of the riflescope in accordance with local regulations regarding electronic waste and optical devices.
- Do not dispose of the riflescope in regular household waste.
- Consider recycling options for the materials used in the riflescope, if available.

Contact Information for Further Support

For any safety inquiries or concerns regarding the 3-27x56 PM II High Power riflescope, please reach out to the manufacturer or your point of purchase for assistance. Always ensure to keep your purchase receipt and any warranty information for reference.

Conclusion

By following these safety instructions and guidelines, you can ensure the safe and effective use of your 3-27x56 PM II High Power riflescope. Your safety and the safety of others is paramount. Thank you for your attention to these important safety measures.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk