

# 3-27x56 PM II High Power - 3-27x56 PM II High Power LP P4FL 1cm cw DT35 MTC LT / ST ZC CT RAL 8000

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-27×56 PM II High Power from Schmidt and Bender is a premier tactical riflescope engineered for ultimate versatility—capable of precise performance from near-range engagements all the way to extreme long-distance targets. With an expansive 3-27× magnification range, this scope adapts effortlessly across calibres and mission profiles.

Its 56 mm objective lens offers exceptional light gathering and clarity, enabling detailed target acquisition even at great distances. The field of view spans approximately 13.0–1.4 m at 100 m, while the exit pupil ranges around 8.7–2.1 mm. Generous eye relief of around 90 mm ensures comfortable alignment and a stable sight picture.

Built on a rugged 34 mm main tube, the scope is constructed for demanding environments. The turret system accommodates ultra-fine click values (e.g., ~0.1 mrad) and massive internal adjustment ranges for elevation and windage—making it suitable for long-range engagement scenarios. Parallax adjustment commonly spans from around 10 m to infinity, giving flexibility across varied target distances.

Key Specifications:

Magnification: 3-27×

Objective Lens Diameter: 56 mm

Main Tube Diameter: 34 mm

Field of View: approx. 13.0-1.4 m @100 m

Exit Pupil: approx. 8.7-2.1 mm

Eye Relief: approx. 90 mm

Click Value: approx. 0.1 mrad (~0.5 cm @100 m) depending on configuration

Parallax: from ~10 m to infinity

Crafted with German precision, the 3-27×56 PM II High Power is ideal for professionals, competition marksmen or hunters who demand the highest optical clarity, mechanical resilience and full versatility across a wide range of engagement distances.

## Attributes

- Name: [3-27x56 PM II High Power LP P4FL 1cm cw DT35 MTC LT / ST ZC CT RAL 8000](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015964
- Mfr. No.: 669-945-972-F2-E9
- Colour: FDE
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537065121

NO IMAGE  
AVAILABLE

# Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 3-27x56 PM II High Power](#)
- [About Us](#)

# Safety Instruction Guide for the 3-27x56 PM II High Power

## Introduction

Thank you for choosing the 3-27x56 PM II High Power riflescope from Schmidt and Bender. This guide provides essential safety instructions to ensure the safe and effective use of your product. Please read this guide carefully before using the riflescope.

## General Safety Guidelines

- **Product Safety:** Ensure safe use of the riflescope by following all instructions and safety precautions outlined in this guide.
- **Enhanced Recalls:** Stay informed about any recall notices related to your product. If a recall occurs, follow the instructions provided for safe return or remedy.
- **Online Shopping:** If purchased online, ensure the platform complies with safety regulations applicable to physical stores.
- **Special Consumer Focus:** Extra care should be taken when the product is used by or around vulnerable groups, such as children.
- **EU Contact Point:** For safety inquiries, refer to the manufacturer or retailer as they are required to provide an EU-based contact.
- **Rapid Alerts:** Regularly check the EU's Safety Gate platform for updates on unsafe products.

## Specific Safety Precautions for Use

- **Avoid Direct Eye Exposure:** Never look directly at the sun or any bright light source through the riflescope, as it may cause severe eye damage.
- **Proper Mounting:** Ensure the riflescope is securely mounted to the firearm to prevent accidents during use.
- **Check for Damage:** Before each use, inspect the riflescope for any signs of damage or wear. Do not use if damaged.
- **Safe Handling:** Always treat the firearm as if it is loaded. Keep the muzzle pointed in a safe direction at all times.
- **Child Safety:** Keep the riflescope and firearm out of reach of children. Educate children about the dangers of firearms.
- **Environmental Conditions:** Avoid using the riflescope in extreme weather conditions that may affect its performance, such as heavy rain or fog.

## Instructions for Installation and Usage

- **Installation:**
  1. Ensure the firearm is unloaded and pointed in a safe direction.
  2. Mount the riflescope onto the firearm's rail or mounting system according to the manufacturer's instructions.
  3. Tighten all screws and mounts securely to prevent movement during use.
  4. Align the riflescope for proper eye relief and ensure it is level.
- **Usage:**
  1. Adjust the magnification according to your target distance using the zoom ring.
  2. Focus the reticle by adjusting the ocular lens until the reticle appears sharp.
  3. Use the turret system for elevation and windage adjustments as needed.

4. Always check your surroundings before taking a shot to ensure safety.

## Disposal Instructions

- **Environmental Considerations:** Dispose of the riflescope and any associated materials in accordance with local regulations for electronic waste.
- **Battery Disposal:** If the riflescope uses batteries, ensure they are disposed of properly at designated battery recycling locations.

## Contact Information for Further Support

For further support, please refer to the manufacturer's website or contact your retailer for assistance with your 3-27x56 PM II High Power riflescope.

By following these safety instructions, you can enjoy the full benefits of your riflescope while ensuring your safety and the safety of others. Thank you for your attention to these important guidelines.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)