

3-27x56 PM II High Power - 3-27x56 PM II High Power LP MSR2 1cm cw DT35 MTC LT / ST ZC CT RAL 8000

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-27x56 PM II High Power from Schmidt and Bender is a premier tactical riflescope engineered for ultimate versatility—capable of precise performance from near-range engagements all the way to extreme long-distance targets. With an expansive 3-27x magnification range, this scope adapts effortlessly across calibres and mission profiles.

Its 56 mm objective lens offers exceptional light gathering and clarity, enabling detailed target acquisition even at great distances. The field of view spans approximately 13.0-1.4 m at 100 m, while the exit pupil ranges around 8.7-2.1 mm. Generous eye relief of around 90 mm ensures comfortable alignment and a stable sight picture.

Built on a rugged 34 mm main tube, the scope is constructed for demanding environments. The turret system accommodates ultra-fine click values (e.g., ~0.1 mrad) and massive internal adjustment ranges for elevation and windage—making it suitable for long-range engagement scenarios. Parallax adjustment commonly spans from around 10 m to infinity, giving flexibility across varied target distances.

Key Specifications:

Magnification: 3-27x

Objective Lens Diameter: 56 mm

Main Tube Diameter: 34 mm

Field of View: approx. 13.0-1.4 m @100 m

Exit Pupil: approx. 8.7-2.1 mm

Eye Relief: approx. 90 mm

Click Value: approx. 0.1 mrad (~0.5 cm @100 m) depending on configuration

Parallax: from ~10 m to infinity

Crafted with German precision, the 3-27x56 PM II High Power is ideal for professionals, competition marksmen or hunters who demand the highest optical clarity, mechanical resilience and full versatility across a wide range of engagement distances.

Attributes

- Name: [3-27x56 PM II High Power LP MSR2 1cm cw DT35 MTC LT / ST ZC CT RAL 8000](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015965
- Mfr. No.: 669-945-842-F2-E9
- Colour: FDE
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537065152

NO IMAGE
AVAILABLE

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 3-27x56 PM II High Power Riflescope](#)
- [About Us](#)

Safety Instruction Guide for the 3-27x56 PM II High Power Riflescope

Introduction

Thank you for choosing the 3-27x56 PM II High Power Riflescope by Schmidt and Bender. This guide provides essential safety instructions to ensure the safe and effective use of your riflescope. Please read this guide carefully and follow all instructions to maximize your safety and performance.

General Safety Guidelines

- Always handle your riflescope with care to avoid damage.
- Ensure the riflescope is securely mounted to your firearm before use.
- Use the riflescope only for its intended purpose—aiming and shooting.
- Keep the riflescope and all accessories out of reach of children.
- Regularly inspect your riflescope for any signs of damage or wear.
- Store the riflescope in a cool, dry place when not in use.
- Be aware of your surroundings and ensure a safe shooting environment.

Specific Safety Precautions for Use

- Always ensure the firearm is unloaded when mounting or adjusting the riflescope.
- Do not look directly at the sun through the riflescope as this may cause permanent eye damage.
- Avoid using the riflescope in extreme weather conditions that may affect its performance.
- Use protective lens covers when the riflescope is not in use to prevent scratches and dust accumulation.
- Ensure that the exit pupil is properly adjusted to avoid eye strain.
- Familiarize yourself with the turret system and make adjustments only when necessary.
- Be cautious of the recoil from your firearm; ensure your eye relief is adequate to prevent injury.

Instructions for Installation and Usage

1. Installation:

- Ensure you have the necessary tools for mounting the riflescope.
- Securely attach the riflescope to the firearm's mounting base according to the manufacturer's instructions.
- Confirm that the riflescope is level and properly aligned with the bore of the firearm.
- Tighten all screws and mounts to the manufacturer's specifications.

2. Usage:

- Adjust the magnification according to your shooting distance and target size.
- Use the parallax adjustment feature to ensure clarity at varying distances.
- Take time to practice with your riflescope to become familiar with its features and adjustments.
- Always maintain a proper shooting stance and ensure the firearm is pointed in a safe direction.

Disposal Instructions

- Dispose of the riflescope and any accessories in accordance with local regulations.
- Do not dispose of the riflescope in household waste.
- Consider recycling options for materials where applicable.

Contact Information for Further Support

For any safety inquiries or concerns regarding your riflescope, please refer to the manufacturer's website or customer support resources. It is important to stay informed about any updates or recalls related to your product.

Conclusion

By following these guidelines, you can ensure the safe and effective use of your 3-27x56 PM II High Power Riflescope. Always prioritize safety and remain informed about best practices for firearm and optics usage. Thank you for your attention to these important safety instructions.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk