

3-27x56 PM II High Power - 3-27x56 PM II High Power LP GR²ID 1cm cw DT35 MTC LT / ST ZC CT RAL 8000

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-27×56 PM II High Power from Schmidt and Bender is a premier tactical riflescope engineered for ultimate versatility—capable of precise performance from near-range engagements all the way to extreme long-distance targets. With an expansive 3-27× magnification range, this scope adapts effortlessly across calibres and mission profiles.

Its 56 mm objective lens offers exceptional light gathering and clarity, enabling detailed target acquisition even at great distances. The field of view spans approximately 13.0–1.4 m at 100 m, while the exit pupil ranges around 8.7–2.1 mm. Generous eye relief of around 90 mm ensures comfortable alignment and a stable sight picture.

Built on a rugged 34 mm main tube, the scope is constructed for demanding environments. The turret system accommodates ultra-fine click values (e.g., ~0.1 mrad) and massive internal adjustment ranges for elevation and windage—making it suitable for long-range engagement scenarios. Parallax adjustment commonly spans from around 10 m to infinity, giving flexibility across varied target distances.

Key Specifications:

Magnification: 3-27×

Objective Lens Diameter: 56 mm

Main Tube Diameter: 34 mm

Field of View: approx. 13.0-1.4 m @100 m

Exit Pupil: approx. 8.7-2.1 mm

Eye Relief: approx. 90 mm

Click Value: approx. 0.1 mrad (~0.5 cm @100 m) depending on configuration

Parallax: from ~10 m to infinity

Crafted with German precision, the 3-27×56 PM II High Power is ideal for professionals, competition marksmen or hunters who demand the highest optical clarity, mechanical resilience and full versatility across a wide range of engagement distances.

Attributes

- Name: [3-27x56 PM II High Power LP GR²ID 1cm cw DT35 MTC LT / ST ZC CT RAL 8000](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015966
- Mfr. No.: 669-945-422-F2-E9
- Colour: FDE
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537065145

NO IMAGE
AVAILABLE

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for 3-27x56 PM II High Power](#)
- [About Us](#)

Safety Instruction Guide for 3-27x56 PM II High Power

Introduction

Thank you for choosing the 3-27x56 PM II High Power riflescope from Schmidt and Bender. This guide is designed to help you use this product safely and effectively while ensuring compliance with EU General Product Safety Regulations (GPSR). Please read this document carefully before using the product.

General Safety Guidelines

- Ensure that the product is used in accordance with the manufacturer's instructions.
- Keep the product out of reach of children and vulnerable individuals.
- Inspect the product regularly for any signs of damage or wear.
- Do not use the product if it appears damaged or malfunctioning.
- Report any unsafe conditions or incidents to the appropriate authorities.
- Stay informed about product recalls and safety updates via the EU's Safety Gate platform.

Specific Safety Precautions for Use

- Always use the riflescope in a safe environment, free from distractions and hazards.
- Ensure that the riflescope is securely mounted to the firearm according to the manufacturer's instructions.
- Avoid looking directly at the sun through the riflescope, as this can cause serious eye damage.
- Be aware of your surroundings and ensure a safe backstop when engaging targets.
- Use appropriate eye protection while using the riflescope.
- Never point the riflescope at anything you do not intend to shoot.
- Follow all local laws and regulations regarding the use of firearms and riflescopes.

Instructions for Installation and Usage

1. Installation:

- Ensure the firearm is unloaded before beginning installation.
- Mount the riflescope onto the firearm's rail using the provided mounting hardware.
- Align the riflescope properly to achieve the desired eye relief.
- Tighten the mounting screws securely but do not overtighten.

2. Usage:

- Adjust the magnification according to your shooting requirements by turning the magnification ring.
- Focus the reticle by adjusting the eyepiece until the reticle appears sharp.
- Use the turret system to make elevation and windage adjustments as needed.
- Regularly check the parallax adjustment to ensure accuracy at varying distances.

3. Maintenance:

- Clean the lenses with a soft, dry cloth. Avoid using harsh chemicals or abrasive materials.
- Store the riflescope in a dry, cool place when not in use.
- Inspect the product periodically for any signs of wear or damage.

Disposal Instructions

- Dispose of the product in accordance with local regulations regarding electronic waste and hazardous materials.
- Do not dispose of the product in regular household waste.
- Contact your local waste disposal authority for information on proper disposal methods.

Contact Information for Further Support

For any inquiries or additional support regarding the 3-27x56 PM II High Power, please refer to the manufacturer's website or customer service for assistance.

By following these guidelines, you can ensure the safe and effective use of your 3-27x56 PM II High Power riflescope. Enjoy your shooting experience!

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk