

3-27x56 PM II High Power - 3-27x56 PM II High Power LP TREMOR3 1cm cw DT35 MTC LT / ST ZC CT RAL 8000

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-27×56 PM II High Power from Schmidt and Bender is a premier tactical riflescope engineered for ultimate versatility—capable of precise performance from near-range engagements all the way to extreme long-distance targets. With an expansive 3-27× magnification range, this scope adapts effortlessly across calibres and mission profiles.

Its 56 mm objective lens offers exceptional light gathering and clarity, enabling detailed target acquisition even at great distances. The field of view spans approximately 13.0–1.4 m at 100 m, while the exit pupil ranges around 8.7–2.1 mm. Generous eye relief of around 90 mm ensures comfortable alignment and a stable sight picture.

Built on a rugged 34 mm main tube, the scope is constructed for demanding environments. The turret system accommodates ultra-fine click values (e.g., ~0.1 mrad) and massive internal adjustment ranges for elevation and windage—making it suitable for long-range engagement scenarios. Parallax adjustment commonly spans from around 10 m to infinity, giving flexibility across varied target distances.

Key Specifications:

Magnification: 3-27×

Objective Lens Diameter: 56 mm

Main Tube Diameter: 34 mm

Field of View: approx. 13.0-1.4 m @100 m

Exit Pupil: approx. 8.7-2.1 mm

Eye Relief: approx. 90 mm

Click Value: approx. 0.1 mrad (~0.5 cm @100 m) depending on configuration

Parallax: from ~10 m to infinity

Crafted with German precision, the 3-27×56 PM II High Power is ideal for professionals, competition marksmen or hunters who demand the highest optical clarity, mechanical resilience and full versatility across a wide range of engagement distances.

Attributes

- Name: [3-27x56 PM II High Power LP TREMOR3 1cm cw DT35 MTC LT / ST ZC CT RAL 8000](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015967
- Mfr. No.: 669-945-532-F2-E9
- Colour: FDE
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537065114

NO IMAGE
AVAILABLE

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 3-27x56 PM II High Power Riflescope](#)
- [About Us](#)

Safety Instruction Guide for the 3-27x56 PM II High Power Riflescope

Introduction

Thank you for choosing the 3-27x56 PM II High Power Riflescope by Schmidt and Bender. This guide is designed to provide you with essential safety information and instructions for the proper use and maintenance of your riflescope. Adhering to these guidelines will help ensure safe and effective performance.

General Safety Guidelines

- Always handle the riflescope with care to avoid damage.
- Ensure that your riflescope is used in accordance with all local laws and regulations.
- Be aware of your surroundings when using the riflescope to avoid accidents.
- Keep the riflescope out of reach of children and vulnerable individuals.
- Regularly check for any signs of wear or damage and address them immediately.
- Report any unsafe conditions or incidents to the appropriate authorities.

Specific Safety Precautions for Use

- **Avoid Eye Injury:** Always use the riflescope with proper eye protection. Ensure that the eye relief is correctly adjusted to prevent injury during use.
- **Check Mounting:** Ensure that the riflescope is securely mounted to your firearm before use. A loose mounting can lead to misalignment and potential accidents.
- **Weather Conditions:** Avoid using the riflescope in extreme weather conditions that may affect visibility or performance.
- **Proper Storage:** Store the riflescope in a cool, dry place when not in use. Avoid exposure to moisture or extreme temperatures.
- **Cleaning:** Use only approved cleaning materials and methods to maintain the lenses and exterior of the riflescope. Avoid harsh chemicals that may damage the lens coatings.

Instructions for Installation and Usage

1. Installation:

- Select a suitable mounting base for your firearm.
- Securely attach the riflescope to the mounting base, ensuring that it is level and properly aligned.
- Tighten the mounting screws according to the manufacturer's specifications to prevent movement during use.

2. Adjusting the Scope:

- Set the magnification to the desired level using the zoom adjustment ring.
- Adjust the focus by turning the objective lens until the target is clear.
- Use the turret system to make precise adjustments for elevation and windage as needed.

3. Using the Riflescope:

- Position your eye at the correct distance from the eyepiece to utilize the full field of view.
- Maintain a stable shooting position to enhance accuracy.
- Be mindful of your surroundings and ensure that your target is safe to engage.

Disposal Instructions

- Dispose of the riflescope in accordance with local regulations regarding electronic waste and materials.
- If the riflescope is damaged beyond repair, consider recycling components wherever possible.
- Do not dispose of the riflescope in regular household waste.

Contact Information for Further Support

For any inquiries regarding safety or usage of the 3-27x56 PM II High Power Riflescope, please refer to the manufacturer's website or contact the designated support service in your region.

Thank you for your attention to these safety instructions. Enjoy the precision and performance of your new riflescope while ensuring safe practices.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk