

3-27x56 PM II High Power - 3-27x56 PM II High Power LP P4FL 1cm ccw DT27 MTC LT / ST ZC CT RAL 8000

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-27×56 PM II High Power from Schmidt and Bender is a premier tactical riflescope engineered for ultimate versatility—capable of precise performance from near-range engagements all the way to extreme long-distance targets. With an expansive 3-27× magnification range, this scope adapts effortlessly across calibres and mission profiles.

Its 56 mm objective lens offers exceptional light gathering and clarity, enabling detailed target acquisition even at great distances. The field of view spans approximately 13.0–1.4 m at 100 m, while the exit pupil ranges around 8.7–2.1 mm. Generous eye relief of around 90 mm ensures comfortable alignment and a stable sight picture.

Built on a rugged 34 mm main tube, the scope is constructed for demanding environments. The turret system accommodates ultra-fine click values (e.g., ~0.1 mrad) and massive internal adjustment ranges for elevation and windage—making it suitable for long-range engagement scenarios. Parallax adjustment commonly spans from around 10 m to infinity, giving flexibility across varied target distances.

Key Specifications:

Magnification: 3-27×

Objective Lens Diameter: 56 mm

Main Tube Diameter: 34 mm

Field of View: approx. 13.0-1.4 m @100 m

Exit Pupil: approx. 8.7-2.1 mm

Eye Relief: approx. 90 mm

Click Value: approx. 0.1 mrad (~0.5 cm @100 m) depending on configuration

Parallax: from ~10 m to infinity

Crafted with German precision, the 3-27×56 PM II High Power is ideal for professionals, competition marksmen or hunters who demand the highest optical clarity, mechanical resilience and full versatility across a wide range of engagement distances.

Attributes

- Name: [3-27x56 PM II High Power LP P4FL 1cm ccw DT27 MTC LT / ST ZC CT RAL 8000](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015968
- Mfr. No.: 669-945-972-G8-E8
- Colour: FDE
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537064971

NO IMAGE
AVAILABLE

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 3-27x56 PM II High Power](#)
- [About Us](#)

Safety Instruction Guide for the 3-27x56 PM II High Power

Introduction

Thank you for choosing the 3-27x56 PM II High Power riflescope from Schmidt and Bender. This guide provides essential safety instructions to ensure safe and effective use of your product. Please read this guide carefully before using the scope to understand the necessary precautions and recommendations.

General Safety Guidelines

- Always handle the riflescope with care to avoid damage.
- Ensure that the scope is mounted securely to prevent it from becoming loose during use.
- Be aware of your surroundings when using the riflescope, especially in outdoor environments.
- Use the riflescope only for its intended purpose as a tactical optical sight.
- Keep the riflescope out of reach of children and unauthorized users.
- Regularly inspect the scope for any signs of damage or wear.
- Follow all local laws and regulations concerning the use of firearms and optical equipment.

Specific Safety Precautions for Use

- Do not look directly at the sun or any bright light sources through the riflescope, as this may cause permanent eye damage.
- Ensure that the exit pupil is properly aligned with your eye to avoid discomfort and to maintain a clear sight picture.
- Always use appropriate eye protection when engaging in shooting activities.
- Be cautious of recoil when firing, as it may affect the stability of the riflescope.
- If the scope becomes damaged or malfunctions, cease use immediately and consult a qualified technician for repairs.
- Avoid using the scope in extreme temperatures or environments that may affect its performance.

Instructions for Installation and Usage

1. Mounting the Scope

- Select a compatible mounting base for your rifle.
- Securely attach the scope to the mounting base according to the manufacturer's instructions.
- Ensure that the scope is level and properly aligned with the rifle's bore.

2. Adjusting the Scope

- Adjust the magnification by rotating the magnification ring until the desired level is achieved.
- Use the turret system to make fine adjustments for elevation and windage.
- Make sure to reset the turrets to zero after making adjustments for future reference.

3. Using the Scope

- Position your eye behind the scope and adjust the focus to achieve a clear view of the target.
- Check the field of view and adjust your position as necessary to maintain a clear sight picture.
- When ready to shoot, ensure that the area is clear of obstructions and that you have a safe backdrop.

4. PostUse Care

- Clean the lenses with a soft cloth to remove any dirt or smudges.
- Store the scope in a protective case when not in use to prevent damage.
- Regularly check for any loose components and tighten them as necessary.

Disposal Instructions

- Dispose of the riflescope in accordance with local regulations for electronic waste.
- Do not dispose of the product in regular household waste.
- If the scope is no longer usable, consider returning it to the manufacturer or a designated recycling center for proper disposal.

Contact Information for Further Support

For any safety inquiries or further support regarding the 3-27x56 PM II High Power riflescope, please refer to the manufacturer's contact points available on their official website or product packaging.

Conclusion

By following these safety instructions, you can ensure a safe and enjoyable experience with your 3-27x56 PM II High Power riflescope. Remember to stay informed about safety updates and recalls through the EU's Safety Gate platform. Thank you for your attention to these important safety guidelines.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk