

3-27x56 PM II High Power - 3-27x56 PM II High Power LP MSR2 1cm ccw DT27 MTC LT / ST ZC CT RAL 8000

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-27×56 PM II High Power from Schmidt and Bender is a premier tactical riflescope engineered for ultimate versatility—capable of precise performance from near-range engagements all the way to extreme long-distance targets. With an expansive 3-27× magnification range, this scope adapts effortlessly across calibres and mission profiles.

Its 56 mm objective lens offers exceptional light gathering and clarity, enabling detailed target acquisition even at great distances. The field of view spans approximately 13.0–1.4 m at 100 m, while the exit pupil ranges around 8.7–2.1 mm. Generous eye relief of around 90 mm ensures comfortable alignment and a stable sight picture.

Built on a rugged 34 mm main tube, the scope is constructed for demanding environments. The turret system accommodates ultra-fine click values (e.g., ~0.1 mrad) and massive internal adjustment ranges for elevation and windage—making it suitable for long-range engagement scenarios. Parallax adjustment commonly spans from around 10 m to infinity, giving flexibility across varied target distances.

Key Specifications:

Magnification: 3-27×

Objective Lens Diameter: 56 mm

Main Tube Diameter: 34 mm

Field of View: approx. 13.0-1.4 m @100 m

Exit Pupil: approx. 8.7-2.1 mm

Eye Relief: approx. 90 mm

Click Value: approx. 0.1 mrad (~0.5 cm @100 m) depending on configuration

Parallax: from ~10 m to infinity

Crafted with German precision, the 3-27×56 PM II High Power is ideal for professionals, competition marksmen or hunters who demand the highest optical clarity, mechanical resilience and full versatility across a wide range of engagement distances.

Attributes

- Name: [3-27x56 PM II High Power LP MSR2 1cm ccw DT27 MTC LT / ST ZC CT RAL 8000](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015969
- Mfr. No.: 669-945-842-G8-E8
- Colour: FDE
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537065008

NO IMAGE
AVAILABLE

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 3-27x56 PM II High Power](#)
- [About Us](#)

Safety Instruction Guide for the 3-27x56 PM II High Power

Introduction

Thank you for choosing the 3-27x56 PM II High Power riflescope from Schmidt and Bender. This guide provides important safety information and instructions to ensure the safe and effective use of your product. Please read this guide carefully before using the product.

General Safety Guidelines

- Always handle the riflescope with care to avoid damage.
- Ensure that the riflescope is mounted securely to your firearm before use.
- Do not look directly at the sun through the riflescope, as this may cause permanent eye damage.
- Keep the riflescope and all related equipment out of reach of children and unauthorized users.
- Regularly inspect the riflescope for any signs of damage or wear. If any issues are found, cease use immediately and seek professional assistance.
- Be aware of your surroundings and ensure that you have a clear line of sight before taking any shots.

Specific Safety Precautions for Use

- **Age Restrictions:** This product is intended for use by individuals aged 18 and older. Ensure that minors are supervised when using or handling the riflescope.
- **Environmental Considerations:** Avoid using the riflescope in extreme weather conditions, such as heavy rain or snow, which may affect its performance.
- **Proper Storage:** When not in use, store the riflescope in a dry, cool place. Use a protective cover to prevent dust and scratches on the lenses.
- **Cleaning:** Use a soft, lintfree cloth to clean the lenses. Avoid using harsh chemicals or abrasive materials that could damage the optics.
- **Mounting:** Follow the manufacturer's instructions when mounting the riflescope. Ensure that all screws and attachments are tightened securely.

Instructions for Installation and Usage

1. Mounting the Riflescope:

- Select an appropriate mounting base that is compatible with your firearm.
- Securely attach the mounting rings to the base.
- Carefully place the riflescope into the rings and tighten them evenly to ensure proper alignment.

2. Adjusting the Scope:

- Use the turret system to adjust for elevation and windage. Turn the turrets according to the manufacturer's specifications for precise adjustments.
- Familiarize yourself with the click values (approx. 0.1 mrad) for accurate shooting.

3. Parallax Adjustment:

- Adjust the parallax setting according to the distance of your target, typically from around 10 m to infinity.
- Ensure that the image is clear and focused before taking any shots.

4. Eye Relief:

- Maintain a distance of approximately 90 mm from the eyepiece to your eye for optimal comfort and safety.
- Ensure that your eye is positioned correctly to avoid any recoil injuries.

5. Field of View:

- Be aware that the field of view spans approximately 13.0–1.4 m at 100 m. Adjust your position as necessary to maintain a clear view of your target.

Disposal Instructions

- Dispose of the riflescope in accordance with local regulations regarding electronic waste and hazardous materials.
- If the product is damaged beyond repair, ensure that it is recycled or disposed of safely to prevent environmental harm.

Contact Information for Further Support

For any inquiries regarding safety or product support, please refer to the manufacturer's customer service options available on their official website or product documentation.

Thank you for your attention to these safety guidelines. By following these instructions, you can ensure a safe and enjoyable experience with your 3–27x56 PM II High Power riflescope.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk