

# 3-27x56 PM II High Power - 3-27x56 PM II High Power LP TREMOR3 1cm ccw DT35 MTC LT / ST ZC CT RAL 8000

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-27×56 PM II High Power from Schmidt and Bender is a premier tactical riflescope engineered for ultimate versatility—capable of precise performance from near-range engagements all the way to extreme long-distance targets. With an expansive 3-27× magnification range, this scope adapts effortlessly across calibres and mission profiles.

Its 56 mm objective lens offers exceptional light gathering and clarity, enabling detailed target acquisition even at great distances. The field of view spans approximately 13.0–1.4 m at 100 m, while the exit pupil ranges around 8.7–2.1 mm. Generous eye relief of around 90 mm ensures comfortable alignment and a stable sight picture.

Built on a rugged 34 mm main tube, the scope is constructed for demanding environments. The turret system accommodates ultra-fine click values (e.g., ~0.1 mrad) and massive internal adjustment ranges for elevation and windage—making it suitable for long-range engagement scenarios. Parallax adjustment commonly spans from around 10 m to infinity, giving flexibility across varied target distances.

Key Specifications:

Magnification: 3-27×

Objective Lens Diameter: 56 mm

Main Tube Diameter: 34 mm

Field of View: approx. 13.0-1.4 m @100 m

Exit Pupil: approx. 8.7-2.1 mm

Eye Relief: approx. 90 mm

Click Value: approx. 0.1 mrad (~0.5 cm @100 m) depending on configuration

Parallax: from ~10 m to infinity

Crafted with German precision, the 3-27×56 PM II High Power is ideal for professionals, competition marksmen or hunters who demand the highest optical clarity, mechanical resilience and full versatility across a wide range of engagement distances.

## Attributes

- Name: [3-27x56 PM II High Power LP TREMOR3 1cm ccw DT35 MTC LT / ST ZC CT RAL 8000](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015975
- Mfr. No.: 669-945-532-F1-E8
- Colour: FDE
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537065060

NO IMAGE  
AVAILABLE

# Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 3-27x56 PM II High Power Riflescope](#)
- [About Us](#)

# Safety Instruction Guide for the 3-27x56 PM II High Power Riflescope

## Introduction

Thank you for choosing the 3-27x56 PM II High Power Riflescope from Schmidt and Bender. This guide provides essential safety instructions to ensure the safe and effective use of your riflescope. It is important to read and understand these instructions before using the product.

## General Safety Guidelines

- Ensure safe use of the riflescope by following these guidelines:
  - Always handle the riflescope with care to prevent damage.
  - Use the riflescope only for its intended purpose—tactical shooting, competition, or hunting.
  - Store the riflescope in a safe, dry place when not in use.
  - Regularly inspect the riflescope for any signs of damage or wear.
  - Keep the riflescope out of reach of children and unauthorized users.

## Specific Safety Precautions for Use

- Before using the riflescope, observe the following precautions:
  - Do not look directly at the sun through the riflescope, as this can cause permanent eye damage.
  - Ensure that the riflescope is securely mounted to your firearm before use.
  - Be aware of your surroundings and ensure a clear line of sight before firing.
  - Use appropriate eye and ear protection while using the riflescope.
  - Follow all local laws and regulations regarding firearms and shooting.

## Instructions for Installation and Usage

- To install and use the 3-27x56 PM II High Power Riflescope, follow these steps:
  - 1. Installation:**
    - Select a suitable mounting base for your firearm.
    - Securely attach the riflescope to the mounting base according to the manufacturer's instructions.
    - Ensure that all screws and mounts are tightened properly.
  - 2. Adjustment:**
    - Adjust the magnification by rotating the magnification ring to your desired level (3-27x).
    - Use the turret system to make adjustments for elevation and windage as needed.
  - 3. Parallax Adjustment:**
    - Adjust the parallax setting to match the distance of your target, ranging from approximately 10 m to infinity.
  - 4. Usage:**
    - Align your eye with the eyepiece to achieve a clear sight picture.
    - Maintain a comfortable shooting position and use the generous eye relief of approximately 90 mm.
    - Always verify that the riflescope is properly zeroed before engaging in shooting activities.

## Disposal Instructions

- When disposing of the riflescope, please follow these guidelines:
  - Do not dispose of the riflescope in regular household waste.
  - Check local regulations for the proper disposal of optical devices and electronic components.
  - Consider recycling options or return to the manufacturer if available.

## **Contact Information for Further Support**

- For any safety inquiries or support regarding the 3-27x56 PM II High Power Riflescope, please consult the product documentation or reach out to the manufacturer.

## **Conclusion**

The 3-27x56 PM II High Power Riflescope is designed for precision and versatility. By following these safety instructions, you can ensure a safe and enjoyable experience while using your riflescope. Always prioritize safety and adhere to local regulations when engaging in shooting activities.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)