

5-45x56 PM II High Power - 5-45x56 PM II High Power LP LRR-MIL 0,05 mrad cw MT II MTC LT / DT II+ ZC LT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 5-45x56 PM II High Power is a professional-grade precision optic that merges a high-performance rifle scope with spotting-scope capability. Designed for observation and ultra-long-range engagement, its enormous 9x zoom range (5-45x) makes it equally at home on reconnaissance, match, or tactical platforms where both identification and shot-making accuracy are required.

Engineered for extreme clarity and reach, the 56 mm objective delivers excellent light gathering while the optical system maintains a large usable field of view across the entire zoom range — allowing fast situational awareness at low magnification and razor-sharp detail at high power. The reticle sits in the first focal plane, so hold-offs and subtensions remain precise at any magnification. The model features robust, lockable turrets with fine 0.1 mrad click values and very large usable internal adjustment ranges tailored for extreme-range correction.

Built on a rugged 34 mm main tube, the High Power is constructed for demanding environments: it is fully weatherproof, fogproof and shock-resistant. Despite its long reach, the design balances mechanical strength with practical ergonomics for field use.

Standout Features

- Exceptional 5-45x magnification range for combined observation and precision shooting
- Large 56 mm objective for outstanding light transmission and image resolution
- First focal plane reticle for accurate ranging and holdover at any magnification
- Precision turrets with 0.1 mrad click value and extensive elevation/windage adjustment range
- Side/parallax adjustment for crisp focus from mid-range to extreme distances
- High optical transmission (~90%) and illuminated reticle options for low-light operations
- Robust 34 mm tube, weatherproof and built for professional use

Key Specifications

- Magnification: 5-45x
- Objective diameter: 56 mm
- Main tube diameter: 34 mm
- Field of view: approx. 7.8-0.9 m @ 100 m
- Exit pupil: approx. 8.8-1.2 mm
- Eye relief: 90 mm
- Length: approx. 434 mm
- Weight: approx. 1,130 g
- Reticle: FFP (various tactical reticle options)
- Click value: 0.1 mrad
- Elevation adjustment range: ~27 mrad (internal ~29.6 mrad)
- Windage adjustment range: ±6 mrad (internal ~21.1 mrad)

NO IMAGE
AVAILABLE

Parallax: adjustable

Illumination levels: multiple (illuminated reticle available)

Optical transmission: ~90%

Designed and manufactured to professional standards, the 5-45x56 PM II High Power is the go-to optic for operators and precision shooters who require unmatched versatility, extreme reach and uncompromising optical and mechanical performance.

Attributes

- Name: [5-45x56 PM II High Power LP LRR-MIL 0,05 mrad cw MT II MTC LT / DT II+ ZC LT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015987
- Mfr. No.: 666-911-41C-I2-H6
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537027488

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 5-45x56 PM II High Power](#)
- [About Us](#)

Safety Instruction Guide for the 5-45x56 PM II High Power

Introduction

Thank you for choosing the 5-45x56 PM II High Power. This professionalgrade precision optic is designed for observation and ultralongrange engagement. To ensure safe and effective use of this product, please read and follow these safety instructions carefully.

General Safety Guidelines

- **Product Safety:** This product has been designed to meet safety standards for nonfood items. Always ensure it is used according to the guidelines provided.
- **Enhanced Recalls:** Stay informed about product recalls. If you receive a recall notice, follow the instructions provided to ensure your safety.
- **Online Shopping:** When purchasing online, ensure the platform complies with safety regulations similar to physical stores.
- **Special Consumer Focus:** Extra care should be taken when this product is used around vulnerable groups, such as children. Never allow children to handle the optic without adult supervision.
- **EU Contact Point:** For any safety inquiries, please refer to the contact information provided with your product packaging.
- **Rapid Alerts:** Be aware of the Safety Gate system for updates on unsafe products.

Specific Safety Precautions for Use

- **Hazard Identification:**
 - The optic is designed for highperformance use. Improper handling may cause damage or injury.
 - Avoid looking directly at the sun through the scope, as this can cause serious eye damage.
 - Be cautious of the weight of the optic (approx. 1,130 g). Ensure it is securely mounted to prevent it from falling.
- **Avoiding Hazards:**
 - Always use the optic in a safe environment, free from distractions and hazards.
 - Ensure that the mounting system is secure before use.
 - Regularly inspect the optic for any signs of damage or wear that may affect its performance.
- **AgeSpecific Warnings:**
 - This product is intended for use by adults and should not be used by children without supervision.
 - Ensure that users are trained in the safe handling and operation of highpowered optics.

Instructions for Installation and Usage

- **Installation:**
 - Carefully read the installation instructions provided with your optic.
 - Ensure that the mounting system is compatible with your rifle.
 - Securely attach the optic to the rifle using the appropriate tools, ensuring that it is firmly in place.
- **Usage:**

- Familiarize yourself with the controls and features of the optic before use.
- Always check the reticle and focus settings before engaging in any shooting activity.
- Adjust the magnification and parallax settings according to your shooting needs.
- Use the optic responsibly and in accordance with local laws and regulations regarding firearms and optics.

Disposal Instructions

- **Environmental Considerations:**

- When disposing of the optic, follow local regulations for electronic waste.
- Do not dispose of the optic in regular household waste.
- If the product is damaged or no longer usable, take it to a designated electronic waste recycling facility.

Contact Information for Further Support

For any questions or concerns regarding the 5-45x56 PM II High Power, please refer to the contact information provided with your product packaging. Always ensure you have the latest information and guidelines for safe use.

Thank you for your attention to these safety instructions. Your safety and the effective use of the 5-45x56 PM II High Power are our top priorities. Enjoy your product responsibly!

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk