

# 5-45x56 PM II High Power - 5-45x56 PM II High Power LP P4FL 1cm ccw DT27 MTC LT / ST ZC CT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 5-45×56 PM II High Power is a professional-grade precision optic that merges a high-performance rifle scope with spotting-scope capability. Designed for observation and ultra-long-range engagement, its enormous 9× zoom range (5-45×) makes it equally at home on reconnaissance, match, or tactical platforms where both identification and shot-making accuracy are required.

Engineered for extreme clarity and reach, the 56 mm objective delivers excellent light gathering while the optical system maintains a large usable field of view across the entire zoom range — allowing fast situational awareness at low magnification and razor-sharp detail at high power. The reticle sits in the first focal plane, so hold-offs and subtensions remain precise at any magnification. The model features robust, lockable turrets with fine 0.1 mrad click values and very large usable internal adjustment ranges tailored for extreme-range correction.

Built on a rugged 34 mm main tube, the High Power is constructed for demanding environments: it is fully weatherproof, fogproof and shock-resistant. Despite its long reach, the design balances mechanical strength with practical ergonomics for field use.

## Standout Features

- Exceptional 5-45× magnification range for combined observation and precision shooting
- Large 56 mm objective for outstanding light transmission and image resolution
- First focal plane reticle for accurate ranging and holdover at any magnification
- Precision turrets with 0.1 mrad click value and extensive elevation/windage adjustment range
- Side/parallax adjustment for crisp focus from mid-range to extreme distances
- High optical transmission (~90%) and illuminated reticle options for low-light operations
- Robust 34 mm tube, weatherproof and built for professional use

## Key Specifications

- Magnification: 5-45×
- Objective diameter: 56 mm
- Main tube diameter: 34 mm
- Field of view: approx. 7.8-0.9 m @ 100 m
- Exit pupil: approx. 8.8-1.2 mm
- Eye relief: 90 mm
- Length: approx. 434 mm
- Weight: approx. 1,130 g
- Reticle: FFP (various tactical reticle options)
- Click value: 0.1 mrad
- Elevation adjustment range: ~27 mrad (internal ~29.6 mrad)
- Windage adjustment range: ±6 mrad (internal ~21.1 mrad)

NO IMAGE  
AVAILABLE

Parallax: adjustable

Illumination levels: multiple (illuminated reticle available)

Optical transmission: ~90%

Designed and manufactured to professional standards, the 5-45×56 PM II High Power is the go-to optic for operators and precision shooters who require unmatched versatility, extreme reach and uncompromising optical and mechanical performance.

## Attributes

- Name: [5-45x56 PM II High Power LP P4FL 1cm ccw DT27 MTC LT / ST ZC CT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015989
- Mfr. No.: 666-911-972-G8-E8
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537014655

# Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for 5-45x56 PM II High Power](#)
- [About Us](#)

# Safety Instruction Guide for 5-45x56 PM II High Power

## Introduction

Thank you for choosing the 5-45x56 PM II High Power riflescope. This guide provides essential safety instructions to ensure the safe and effective use of your product. Please read and follow these guidelines carefully to maximize your experience and maintain safety.

## General Safety Guidelines

- **Product Safety:** Ensure safe usage by following all instructions. The 5-45x56 PM II High Power is designed for professional use and should be handled accordingly.
- **Enhanced Recalls:** In the event of a safety issue, be aware that standardized recall notices will be issued. Always check for updates regarding product recalls.
- **Online Shopping:** If purchased online, ensure that the retailer complies with safety requirements equivalent to those of physical stores.
- **Special Consumer Focus:** This product is not intended for use by children. Keep it out of reach of minors.
- **EU Contact Point:** For safety inquiries, refer to the designated EU contact point associated with this product.
- **Rapid Alerts:** Stay informed about product safety updates through the EU's Safety Gate platform.

## Specific Safety Precautions for Use

- **Handling:** Always handle the riflescope with care. Avoid dropping or subjecting it to severe impacts.
- **Mounting:** Ensure the riflescope is properly mounted on your firearm. Follow the manufacturer's instructions for secure attachment.
- **Weather Conditions:** Although the 5-45x56 PM II is weatherproof, avoid exposing it to extreme weather conditions for prolonged periods.
- **Cleaning:** Use only recommended cleaning materials and methods to maintain the optical surfaces. Avoid using abrasive materials.
- **Storage:** Store the riflescope in a dry and secure location when not in use. Use a protective case to prevent damage.
- **Usage:** Always use the riflescope in accordance with local laws and regulations regarding firearms and optics.
- **Optical Safety:** Do not look directly at the sun or bright lights through the riflescope to prevent eye damage.

## Instructions for Installation and Usage

- **Installation:**
  1. Ensure the firearm is unloaded before beginning installation.
  2. Choose a suitable mounting location on your firearm.
  3. Securely attach the riflescope using the provided mounting hardware.
  4. Check alignment and ensure that the turrets are accessible for adjustments.
- **Usage:**
  1. Adjust the magnification to the desired level using the zoom ring.
  2. Focus the riflescope by adjusting the side parallax knob.
  3. Utilize the reticle for accurate aiming and range estimation.

4. Make elevation and windage adjustments using the precision turrets.
5. After use, ensure the riflescope is cleaned and stored properly.

## Disposal Instructions

- **Environmental Considerations:** Dispose of the riflescope in accordance with local regulations regarding electronic waste and optical devices.
- **Recycling:** If applicable, consider recycling components of the product to reduce environmental impact.

## Contact Information for Further Support

For any safety inquiries or further assistance, please refer to the designated EU contact point associated with this product. Always keep documentation and receipts for warranty and support purposes.

Thank you for your attention to these safety instructions. Enjoy your experience with the 5-45x56 PM II High Power riflescope, and remember to prioritize safety at all times.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)