

5-45x56 PM II High Power - 5-45x56 PM II High Power LP P4FL 1cm ccw DT II+ MTC LT / ST II ZC LT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 5-45×56 PM II High Power is a professional-grade precision optic that merges a high-performance rifle scope with spotting-scope capability. Designed for observation and ultra-long-range engagement, its enormous 9× zoom range (5-45×) makes it equally at home on reconnaissance, match, or tactical platforms where both identification and shot-making accuracy are required.

Engineered for extreme clarity and reach, the 56 mm objective delivers excellent light gathering while the optical system maintains a large usable field of view across the entire zoom range — allowing fast situational awareness at low magnification and razor-sharp detail at high power. The reticle sits in the first focal plane, so hold-offs and subtensions remain precise at any magnification. The model features robust, lockable turrets with fine 0.1 mrad click values and very large usable internal adjustment ranges tailored for extreme-range correction.

Built on a rugged 34 mm main tube, the High Power is constructed for demanding environments: it is fully weatherproof, fogproof and shock-resistant. Despite its long reach, the design balances mechanical strength with practical ergonomics for field use.

Standout Features

- Exceptional 5-45× magnification range for combined observation and precision shooting
- Large 56 mm objective for outstanding light transmission and image resolution
- First focal plane reticle for accurate ranging and holdover at any magnification
- Precision turrets with 0.1 mrad click value and extensive elevation/windage adjustment range
- Side/parallax adjustment for crisp focus from mid-range to extreme distances
- High optical transmission (~90%) and illuminated reticle options for low-light operations
- Robust 34 mm tube, weatherproof and built for professional use

Key Specifications

- Magnification: 5-45×
- Objective diameter: 56 mm
- Main tube diameter: 34 mm
- Field of view: approx. 7.8-0.9 m @ 100 m
- Exit pupil: approx. 8.8-1.2 mm
- Eye relief: 90 mm
- Length: approx. 434 mm
- Weight: approx. 1,130 g
- Reticle: FFP (various tactical reticle options)
- Click value: 0.1 mrad
- Elevation adjustment range: ~27 mrad (internal ~29.6 mrad)
- Windage adjustment range: ±6 mrad (internal ~21.1 mrad)

NO IMAGE
AVAILABLE

Parallax: adjustable

Illumination levels: multiple (illuminated reticle available)

Optical transmission: ~90%

Designed and manufactured to professional standards, the 5-45×56 PM II High Power is the go-to optic for operators and precision shooters who require unmatched versatility, extreme reach and uncompromising optical and mechanical performance.

Attributes

- Name: [5-45x56 PM II High Power LP P4FL 1cm ccw DT II+ MTC LT / ST II ZC LT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015994
- Mfr. No.: 666-911-972-L7-I5
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537036671

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for 5-45x56 PM II High Power](#)
- [About Us](#)

Safety Instruction Guide for 5-45x56 PM II High Power

Introduction

Thank you for choosing the 5-45x56 PM II High Power. This highperformance optic is designed for precision shooting and observation. To ensure your safety and the optimal performance of this product, please read and follow the guidelines outlined in this safety instruction guide.

General Safety Guidelines

- **Product Safety:** Ensure safe use of the optic by adhering to all safety instructions. This product is designed for nonfood use and should not be used for any other purpose.
- **Enhanced Recalls:** Be aware that in the event of a safety issue, standardized recall notices will be issued. Stay informed about any recalls that may affect your product.
- **Online Shopping:** If purchased online, ensure that the platform complies with safety requirements similar to those of physical stores.
- **Special Consumer Focus:** Extra care should be taken when the product is used by or around vulnerable groups, including children. Always supervise children when they are near the optic.
- **EU Contact Point:** For safety inquiries, ensure that you have access to the appropriate EUbased contact information.
- **Rapid Alerts:** Stay updated on product safety and recalls through the EU's Safety Gate platform.

Specific Safety Precautions for Use

- **Handling:** Always handle the optic with care. Avoid dropping or subjecting it to strong impacts which may affect its performance.
- **Environment:** Use the optic in environments that are within its operational limits. Avoid exposure to extreme temperatures, humidity, or corrosive substances.
- **Cleaning:** Use a soft, dry cloth to clean the lens. Avoid using harsh chemicals or abrasive materials that could damage the optic.
- **Storage:** Store the optic in a dry, cool place when not in use. Use a protective case to prevent dust and scratches.
- **Usage:** Ensure that the optic is securely mounted on the rifle before use. Regularly check the mounting to ensure it remains secure.

Instructions for Installation and Usage

1. Installation:

- Carefully read the mounting instructions specific to your rifle model.
- Use appropriate tools to securely attach the optic to the rifle.
- Ensure the optic is aligned properly for accurate aiming.

2. Usage:

- Adjust the magnification to the desired level before taking aim.
- Use the reticle for accurate ranging and holdover adjustments.
- Maintain a proper shooting stance and ensure a clear line of sight before firing.

3. Maintenance:

- Regularly check the optic for any signs of damage or wear.

- Ensure that the turrets are functioning properly and that adjustments are smooth.
- If any issues arise, discontinue use and seek professional assistance.

Disposal Instructions

- Dispose of the optic in accordance with local regulations regarding electronic waste and optical devices.
- Do not dispose of the product in regular household waste.
- If applicable, remove batteries and dispose of them separately according to battery disposal guidelines.

Contact Information for Further Support

For any questions or concerns regarding the 5-45x56 PM II High Power, please refer to the manufacturer's website or contact your local retailer for support. Ensure you have the product details available for efficient assistance.

By following these safety guidelines, you can ensure a safe and effective experience with your 5-45x56 PM II High Power optic. Thank you for your attention to these important safety instructions.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk