

GLOCK TRIGGERS (Pull weight 3lb) - GLOCK GEN 3: G17, G17L, G19, G22, G23, G24, G34, G35 GLOCK GEN 4: G17, G19, G22, G23, G34, G35

[Rifle Parts](#) > [Triggers Parts](#) > [Triggers](#)

ULTIMATE BUILDER'S KIT FOR GLOCK GEN 3-4 Starting with Timney's Alpha Competition trigger platform, the Ultimate Builder's Kit (UBK) for Glock Gen 3-4 also includes a striker, striker spring, connector, safety plunger, and safety plunger spring. The striker, made from stainless steel, matches the geometry of the Alpha Competition sear, while the safety plunger matches the geometry of the Alpha Competition trigger bar and is made from tool steel. All Ultimate Builder's Kit parts are heat treated and NP3 coated for durability and increased lubricity. With a factory set pull weight of 2.5 to 3 pounds, the Timney Alpha Competition UBK trigger kit answers the call for a trigger that maintains the feel of a Timney Trigger all while upholding the dependability of the Glock system. Through an improved trigger design, Timney has created an upgraded trigger that retains the reliability of the Glock while offering a lighter pull weight and a smoother feel from the UBK. SPECIFICATIONS: COMPATIBLE WITH: Medium frame, double stack Gen 3-4 PULL WEIGHT: 2.5 – 3lbs. STRIKER: Stainless steel with NP3 coating CONNECTOR: Stainless steel with NP3 coating SAFETY PLUNGER: Tool steel with NP3 coating TRIGGER ASSEMBLY: Alpha Competition Gen 3-4 trigger



Attributes

- Name: [GLOCK GEN 3: G17, G17L, G19, G22, G23, G24, G34, G35 GLOCK GEN 4: G17, G19, G22, G23, G34, G35](#)
- Manufacturer: [TIMNEY](#)
- Product no.: EU2016548
- Mfr. No.: ALPHA GLOCK 3-4 - BRONZE
- Delivery weight: 1kg
- Shipping height: 38mm
- Shipping width: 89mm
- Shipping length: 191mm
- UPC: 081950613687

Table of Contents

- Startpage
- GLOCK TRIGGERS Safety Instruction Guide
- About Us

GLOCK TRIGGERS Safety Instruction Guide

Introduction

Thank you for choosing the GLOCK TRIGGERS (Pull weight 3lb) for your GLOCK Gen 3 and Gen 4 handguns. This guide provides essential safety instructions to ensure the safe and effective use of your product. Please read this guide carefully before installation and use.

General Safety Guidelines

- Ensure the product is compatible with your specific GLOCK model (Gen 34).
- Always handle firearms with care and follow all safety protocols.
- Keep this product out of reach of children and unauthorized users.
- Regularly inspect the product for any signs of wear or damage.
- Report any unsafe conditions or accidents to the appropriate authorities.
- Stay informed about product recalls and safety updates via the EU Safety Gate platform.

Specific Safety Precautions for Use

- Do not modify the GLOCK TRIGGERS beyond the manufacturer's specifications.
- Always use the product in accordance with the manufacturer's instructions.
- Ensure that the firearm is unloaded before installation or maintenance.
- Avoid using the trigger kit in wet or humid conditions to prevent corrosion.
- Use appropriate personal protective equipment (PPE) when handling tools during installation.

Instructions for Installation and Usage

1. Preparation:

- Ensure that you have all components of the Ultimate Builder's Kit (UBK): striker, striker spring, connector, safety plunger, and safety plunger spring.
- Gather necessary tools for installation (e.g., screwdriver, punch tool).

2. Installation Steps:

- **Unload the Firearm:** Make sure your GLOCK is completely unloaded.
- **Remove the Slide:** Follow the manufacturer's guidelines to safely remove the slide from the frame.
- **Install the Striker:**
 - Insert the stainless steel striker into the slide, ensuring it aligns with the trigger mechanism.
- **Install the Striker Spring:** Place the striker spring over the striker.
- **Connect the Connector:** Insert the stainless steel connector into the designated slot.
- **Install the Safety Plunger:**
 - Insert the tool steel safety plunger into its position.
 - Add the safety plunger spring to ensure proper function.
- **Reassemble the Firearm:** Carefully reattach the slide to the frame, ensuring all parts are securely in place.

3. Testing:

- Once installed, conduct a function test to ensure the trigger operates smoothly.
- Confirm the pull weight is between 2.5 to 3 pounds as specified.

4. Usage:

- Always follow safe firearm handling practices.
- Be aware of your surroundings and ensure a clear line of sight when using your firearm.

Disposal Instructions

- Dispose of any packaging materials and old parts in accordance with local regulations.
- Do not dispose of the product in regular household waste. Check for local recycling programs for metal components.

Contact Information for Further Support

For any inquiries regarding safety, usage, or installation, please refer to the manufacturer's website or customer service for assistance.

Thank you for prioritizing safety while using the GLOCK TRIGGERS. Enjoy your enhanced shooting experience!

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk