

BROWNING X-BOLT TRIGGER ****3lb**** (Pull Weight adjustable 1.5-4lb)

[Rifle Parts](#) > [Triggers Parts](#) > [Triggers](#)

You asked and Timney delivered. The Browning X-Bolt Replacement Trigger was developed in response to shooters seeking a cleaner, more precise, and more consistent trigger for the highly popular Browning X-Bolt rifle. This self-contained replacement trigger reuses the factory safety button and safety bar, allowing for a quick and straightforward installation. Please note that installing this trigger disables the rifle's original bolt-lock function.



The trigger comes factory-set at 3 lbs. and is fully adjustable from 2 to 4 lbs., enabling you to fine-tune the pull weight to your personal preference and enjoy the crisp, smooth break Timney is known for.

Features:

- Adjustable pull weight from 2–4 lbs.
- Single-stage design
- Available for X-Bolt and X-Bolt 2 actions
- Enhances accuracy and trigger control
- Simple installation—no gunsmith required
- Hand-assembled, tested, and calibrated
- Covered by Timney's Legendary Lifetime Warranty
- Proudly manufactured in the USA

Compatibility:

Browning X-Bolt and X-Bolt 2 actions

Attributes

- Name: [BROWNING X-BOLT TRIGGER ****3lb**** \(Pull Weight adjustable 1.5-4lb\)](#)
- Manufacturer: [TIMNEY](#)
- Product no.: EU2016588
- Mfr. No.: 603
- Delivery weight: 0.09kg
- Shipping height: 51mm
- Shipping width: 102mm
- Shipping length: 191mm
- UPC: 081950603008

Table of Contents

- [Startpage](#)
- [Browning XBolt Trigger Safety Instruction Guide](#)
- [About Us](#)

Browning XBolt Trigger Safety Instruction Guide

Introduction

Thank you for choosing the Browning XBolt Trigger. This product is designed to enhance your shooting experience by providing a cleaner, more precise trigger pull. Please read this safety instruction guide carefully to ensure safe installation and use of the trigger. Your safety and the safety of others is our top priority.

General Safety Guidelines

- Always treat firearms and firearm components as if they are loaded.
- Keep the firearm pointed in a safe direction at all times.
- Store the firearm and trigger in a secure location, out of reach of children and unauthorized users.
- Use only the Browning XBolt Trigger with compatible Browning XBolt and XBolt 2 actions.
- Regularly inspect your trigger and firearm for any signs of wear or damage.
- Do not use the trigger if it shows any signs of malfunction or if it has been modified.
- Report any unsafe products or accidents to the appropriate authorities.

Specific Safety Precautions for Use

- Ensure that the firearm is unloaded before attempting to install or adjust the trigger.
- Always follow the manufacturer's instructions for installation and adjustment.
- Be aware that installing this trigger disables the rifle's original boltlock function.
- Make sure to adjust the pull weight according to your personal preference, but do not exceed the recommended limits of 2 to 4 lbs.
- If you are unsure about the installation or adjustment process, consult a qualified gunsmith.
- Use proper eye and ear protection when testing the trigger with live ammunition.

Instructions for Installation and Usage

1. Preparation:

- Ensure the firearm is completely unloaded and the workspace is clean and welllit.
- Gather the necessary tools for installation, including a screwdriver and any other tools specified in the manufacturer's instructions.

2. Installation:

- Remove the factory trigger according to the Browning XBolt rifle manual.
- Carefully install the Browning XBolt Trigger, ensuring that it aligns properly with the safety button and safety bar.
- Follow the specific installation steps provided with the trigger to ensure proper function.
- Once installed, doublecheck that all components are secure and functioning correctly.

3. Adjustment:

- The trigger is factoryset at 3 lbs. To adjust the pull weight, follow the adjustment instructions provided with the trigger.
- Use a pull gauge to measure the pull weight accurately.
- Adjust the trigger to your preferred weight within the range of 2 to 4 lbs.

4. Testing:

- After installation and adjustment, conduct a function test in a safe environment.

- Ensure that the trigger functions correctly and that there are no signs of malfunction.

5. Maintenance:

- Regularly clean and inspect the trigger to maintain optimal performance.
- Store the firearm and trigger securely when not in use.

Disposal Instructions

When disposing of the Browning XBolt Trigger, follow these guidelines: * Ensure that the trigger is no longer attached to a firearm. * Dispose of the trigger in accordance with local regulations regarding electronic waste and firearm components. * Do not dispose of the trigger in regular household waste.

Contact Information for Further Support

For any inquiries regarding the Browning XBolt Trigger, please contact the manufacturer or a qualified gunsmith. Ensure you have the product details ready for assistance.

By following these safety instructions, you can enjoy the benefits of your Browning XBolt Trigger while ensuring a safe shooting experience. Thank you for your attention to these important safety guidelines.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk