

Trigger - AR-Safety Selector Shaft for H&K

Engineered to adapt the ERATAC trigger to your HK MR223 or MR308, this safety selector shaft integrates seamlessly with your platform. Please note that the original HK levers and roll pins must be retained for installation. Two spare roll pins are included in the package for your convenience. (Delivery without levers)



Attributes

- Name: AR-Safety Selector Shaft for H&K
- Manufacturer: ERATAC
- Product no.: EU2017847
- Mfr. No.: T0561-0001
- Colour: Black
- Delivery weight: 1kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 100mm
- EAN/UPC: T0561-0001

Table of Contents

- [Startpage](#)
- [English: ERATAC Trigger ARSafety Selector Shaft for H&K Safety Instruction Guide](#)

ERATAC Trigger ARSafety Selector Shaft for H&K Safety Instruction Guide

Introduction

Thank you for choosing the ERATAC Trigger ARSafety Selector Shaft for your HK MR223 or MR308. This product is designed to enhance your firearm's safety features while ensuring seamless integration with your existing platform. Please read this safety instruction guide carefully to ensure safe and effective use of the product.

General Safety Guidelines

- Always handle firearms with care and respect.
- Ensure that the firearm is unloaded before installation or maintenance.
- Store the product and firearm in a secure location, away from children and unauthorized users.
- Regularly inspect the product for any signs of wear or damage.
- Follow all local laws and regulations regarding firearm modifications and safety devices.
- Report any unsafe products or incidents to the appropriate authorities.

Specific Safety Precautions for Use

- Retain the original HK levers and roll pins for installation.
- Use only the spare roll pins provided in the package for any replacements.
- Ensure that the safety selector shaft is correctly installed before using the firearm.
- Do not modify the product or use it in any manner not specified by the manufacturer.
- Always verify that the safety selector is functioning properly before use.
- Be aware of your surroundings and ensure that you are in a safe environment when handling firearms.

Instructions for Installation and Usage

1. Preparation

- Ensure the firearm is unloaded and pointed in a safe direction.
- Gather necessary tools for installation (e.g., screwdriver, pliers).

2. Installation Steps

- Remove the original HK levers and roll pins from the firearm.
- Align the ERATAC safety selector shaft with the designated area on the firearm.
- Insert the provided roll pins to secure the shaft in place.
- Reattach the original HK levers to the safety selector shaft.
- Verify that all components are securely fastened and functioning correctly.

3. Usage Instructions

- To engage the safety, rotate the lever to the "safe" position.
- To disengage the safety, rotate the lever to the "fire" position.
- Always ensure the safety is engaged when the firearm is not in use.

Disposal Instructions

- Dispose of any packaging materials in accordance with local regulations.
- If the product is no longer needed or is damaged beyond repair, dispose of it in a responsible manner, ensuring it does not pose a risk to others.

Contact Information for Further Support

For any questions or concerns regarding the ERATAC Trigger ARSafety Selector Shaft, please refer to the manufacturer's contact information provided with your product packaging. Ensure you have the product details ready for efficient assistance.

Thank you for prioritizing safety and compliance with these guidelines. Enjoy your enhanced firearm experience with the ERATAC Trigger ARSafety Selector Shaft.