

Two-Piece Ring Mounts - ERATAC Ring Mount, 30 mm, H 13mm, nut

Mil-Spec Engineering: Crafted from aircraft-grade, high-strength aluminum and finished with a non-reflective, matte black Mil-Spec Type III hardcoat anodization.



Dual Fastening Options: Choose between a standard nut configuration or a tool-free, quick-detach (QD) safety lever system for rapid mounting and removal.

Adaptable Rail Tension: The adjustable aluminum safety levers can be easily fine-tuned to ensure a rock-solid lock on out-of-spec or non-standard Picatinny rails.

Tactical Modular Interface: Boasting a robust 25 mm ring width, every single ring is equipped with the integrated ERATAC UNIVERSAL interface to support secondary optics and accessories.

Attributes

- Name: ERATAC Ring Mount, 30 mm, H 13mm, nut
- Manufacturer: ERATAC
- Product no.: EU2017948
- Mfr. No.: T5003-0013
- Colour: Black
- Delivery weight: 1kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 100mm
- EAN/UPC: T5003-0013

Table of Contents

- [Startpage](#)
- [English: TwoPiece Ring Mounts ERATAC Ring Mount Safety Instructions](#)

TwoPiece Ring Mounts ERATAC Ring Mount Safety Instructions

Introduction

Thank you for choosing the TwoPiece Ring Mounts ERATAC Ring Mount. This product is designed for secure mounting of optics on firearms. Please read this safety instruction guide carefully to ensure safe and effective use of this product.

General Safety Guidelines

- Ensure that the product is installed and used according to these instructions.
- Always handle the ring mount with care to avoid damage.
- Check the product regularly for signs of wear and tear.
- Do not use the ring mount if it shows any signs of damage or if any components are missing.
- Keep the product out of reach of children and vulnerable individuals to prevent accidents.
- Report any unsafe products or incidents to the appropriate authorities.

Specific Safety Precautions for Use

• Installation Precautions:

- Ensure the firearm is unloaded before installing the ring mount.
- Use only compatible optics with the ring mount specifications.

• Usage Precautions:

- Avoid using the ring mount in extreme temperatures or harsh environments that may affect its integrity.
- Do not exceed the manufacturer's weight limit for mounted optics.

• Maintenance Precautions:

- Clean the ring mount with a soft, dry cloth to avoid scratching the surface.
- Inspect the adjustable aluminum safety levers regularly to ensure they are functioning properly.

Instructions for Installation and Usage

1. Installation:

- Ensure the firearm is unloaded and pointed in a safe direction.
- Select the appropriate Picatinny rail on your firearm for mounting.
- If using the standard nut configuration:
 - Align the ring mount with the rail.
 - Secure the mount using the nut and tighten it to ensure stability.
- If using the quickdetach (QD) safety lever system:
 - Align the mount with the rail.
 - Engage the safety lever until you hear a click, indicating a secure attachment.
- Adjust the aluminum safety levers as necessary to ensure a tight fit on the rail.

2. Usage:

- After installation, check the stability of the mounted optics.

- Always verify that the optics are securely attached before use.
- Regularly check the mount during use to ensure it remains secure.

Disposal Instructions

- Dispose of the product responsibly in accordance with local regulations.
- Do not dispose of the product in household waste. Check for recycling options in your area.
- If the product is damaged beyond repair, ensure that it is disposed of in a manner that prevents harm to the environment.

Contact Information for Further Support

For any inquiries or concerns regarding the TwoPiece Ring Mounts ERATAC Ring Mount, please refer to the manufacturer's contact information provided with your product.

Thank you for following these safety instructions. Your adherence to these guidelines helps ensure a safe and enjoyable experience with your TwoPiece Ring Mounts ERATAC Ring Mount.