

Two-Piece Ring Mounts - ERATAC Ring Mount, 30 mm, H 17mm, nut

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Mount Sets](#)

Mil-Spec Engineering: Crafted from aircraft-grade, high-strength aluminum and finished with a non-reflective, matte black Mil-Spec Type III hardcoat anodization.



Dual Fastening Options: Choose between a standard nut configuration or a tool-free, quick-detach (QD) safety lever system for rapid mounting and removal.

Adaptable Rail Tension: The adjustable aluminum safety levers can be easily fine-tuned to ensure a rock-solid lock on out-of-spec or non-standard Picatinny rails.

Tactical Modular Interface: Boasting a robust 25 mm ring width, every single ring is equipped with the integrated ERATAC UNIVERSAL interface to support secondary optics and accessories.

Attributes

- Name: [ERATAC Ring Mount, 30 mm, H 17mm, nut](#)
- Manufacturer: [ERATAC](#)
- Product no.: EU2017950
- Mfr. No.: T5003-0017
- Colour: Black
- Delivery weight: 1kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 100mm
- EAN/UPC: T5003-0017

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for TwoPiece Ring Mounts ERATAC](#)
- [About Us](#)

Safety Instruction Guide for TwoPiece Ring Mounts ERATAC

Introduction

Thank you for choosing the TwoPiece Ring Mounts ERATAC. This guide provides essential safety instructions to ensure safe use and optimal performance of your product. Please read this manual carefully before installation and usage.

General Safety Guidelines

- Ensure that the product is used only for its intended purpose.
- Regularly inspect the ring mounts for any signs of wear or damage before each use.
- Do not exceed the manufacturer's specified weight limits for mounted optics and accessories.
- Keep the product out of reach of children to prevent accidents.
- Report any unsafe conditions or accidents to the appropriate authorities.

Specific Safety Precautions for Use

- When using the quickdetach (QD) safety lever system, ensure it is fully engaged to prevent accidental detachment.
- Be cautious when adjusting the rail tension. Overtightening may damage the mounts or the rail system.
- Always verify that the ring mounts are securely attached to the firearm before use.
- Avoid using the product in extreme conditions (e.g., high humidity, extreme temperatures) that may affect its performance.

Instructions for Installation and Usage

1. Installation

- Start by cleaning the Picatinny rail to remove any dirt or debris.
- Select the desired position on the rail for mounting.
- If using the standard nut configuration:
 - Align the ring mount with the rail.
 - Securely fasten the nut with a wrench until snug, ensuring the mount does not move.
- If using the quickdetach (QD) safety lever system:
 - Position the ring mount on the rail.
 - Press the safety lever down until it clicks into place, ensuring it is locked.
- Check the alignment of the mounted optic to ensure proper sighting.

2. Usage

- Regularly check the tightness of the mounts during use, especially after heavy shooting sessions.
- If you notice any movement or looseness, stop using the product and retighten as necessary.
- When removing the mount, carefully disengage the QD lever or unscrew the nut, taking care to handle it gently.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the product in regular household waste.
- Consider recycling the aluminum components if possible.

Contact Information for Further Support

For any inquiries related to safety or product performance, please contact the manufacturer or your local dealer. Ensure you have your product details ready for reference.

Thank you for prioritizing safety while using the TwoPiece Ring Mounts ERATAC. Your adherence to these guidelines helps ensure a safe and enjoyable experience.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk