

# Two-Piece Ring Mounts - ERATAC Ring Mount, 34 mm H 18 mm, lever

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Mount Sets](#)

Mil-Spec Engineering: Crafted from aircraft-grade, high-strength aluminum and finished with a non-reflective, matte black Mil-Spec Type III hardcoat anodization.



Dual Fastening Options: Choose between a standard nut configuration or a tool-free, quick-detach (QD) safety lever system for rapid mounting and removal.

Adaptable Rail Tension: The adjustable aluminum safety levers can be easily fine-tuned to ensure a rock-solid lock on out-of-spec or non-standard Picatinny rails.

Tactical Modular Interface: Boasting a robust 25 mm ring width, every single ring is equipped with the integrated ERATAC UNIVERSAL interface to support secondary optics and accessories.

## Attributes

- Name: [ERATAC Ring Mount, 34 mm H 18 mm, lever](#)
- Manufacturer: [ERATAC](#)
- Product no.: EU2017953
- Mfr. No.: T4004-0018
- Colour: Black
- Delivery weight: 1kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 100mm
- EAN/UPC: T4004-0018

# Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for TwoPiece Ring Mounts ERATAC](#)
- [About Us](#)

# Safety Instruction Guide for TwoPiece Ring Mounts ERATAC

## Introduction

Thank you for choosing the TwoPiece Ring Mounts ERATAC. This guide provides important safety instructions and information to ensure the safe and effective use of your product. Please read and follow all guidelines carefully to avoid potential hazards.

## General Safety Guidelines

- Ensure that all components are intact and undamaged before use.
- Use the product only for its intended purpose.
- Keep the product out of reach of children and vulnerable individuals.
- Regularly inspect the ring mounts for wear or damage.
- In case of any malfunction or unusual behavior, cease use immediately and consult a professional.

## Specific Safety Precautions for Use

- Do not exceed the specified load limits of the ring mounts.
- Ensure that the ring mounts are securely attached before use.
- Avoid using the product in extreme weather conditions unless specified.
- Be cautious of sharp edges during installation and handling.
- Use appropriate tools when adjusting or installing the mounts to prevent injury.

## Instructions for Installation and Usage

### 1. Preparation:

- Gather all necessary tools and components.
- Ensure you have a clean, flat workspace.

### 2. Installation:

- Select the desired mounting location on your Picatinny rail.
- If using the standard nut configuration:
  - Align the ring mount over the chosen rail section.
  - Insert the nut and tighten securely with the appropriate tool.
- If using the toolfree, quickdetach (QD) safety lever system:
  - Position the mount on the rail and engage the lever.
  - Ensure it clicks into place and is locked securely.

### 3. Adjustment:

- Use the adjustable aluminum safety levers to finetune the tension.
- Ensure the mount is firmly locked in place before use.

### 4. Usage:

- Attach your optic or accessory to the ring mount.
- Regularly check the tightness of the mount during use, especially after heavy use or movement.

## **Disposal Instructions**

- Dispose of the product in accordance with local regulations.
- Do not dispose of the product in household waste; consider recycling options for aluminum components.

## **Contact Information for Further Support**

For any safety inquiries or support, please refer to the manufacturer's official contact points as specified on the product packaging or documentation.

By adhering to these guidelines, you can ensure a safe experience while using the TwoPiece Ring Mounts ERATAC. Thank you for your attention to these important safety instructions.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)