

Two-Piece Ring Mounts - ERATAC Ring Mount, 34 mm, H 13 mm, lever

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Mount Sets](#)

Mil-Spec Engineering: Crafted from aircraft-grade, high-strength aluminum and finished with a non-reflective, matte black Mil-Spec Type III hardcoat anodization.



Dual Fastening Options: Choose between a standard nut configuration or a tool-free, quick-detach (QD) safety lever system for rapid mounting and removal.

Adaptable Rail Tension: The adjustable aluminum safety levers can be easily fine-tuned to ensure a rock-solid lock on out-of-spec or non-standard Picatinny rails.

Tactical Modular Interface: Boasting a robust 25 mm ring width, every single ring is equipped with the integrated ERATAC UNIVERSAL interface to support secondary optics and accessories.

Attributes

- Name: [ERATAC Ring Mount, 34 mm, H 13 mm, lever](#)
- Manufacturer: [ERATAC](#)
- Product no.: EU2017956
- Mfr. No.: T4004-0013
- Colour: Black
- Delivery weight: 1kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 100mm
- EAN/UPC: T4004-0013

Table of Contents

- [Startpage](#)
- [TwoPiece Ring Mounts ERATAC Safety Instructions](#)
- [About Us](#)

TwoPiece Ring Mounts ERATAC Safety Instructions

Introduction

Thank you for purchasing the TwoPiece Ring Mounts ERATAC. This product is designed to provide a reliable and secure mounting solution for your optics. To ensure safe and effective use, please read and follow these safety instructions carefully.

General Safety Guidelines

- Always ensure that the product is used in accordance with the manufacturer's instructions.
- Inspect the product for any damage or defects before each use.
- Do not modify the product in any way, as this may compromise safety.
- Store the product in a dry and secure location when not in use.
- Keep the product out of reach of children and vulnerable individuals.
- Report any safety concerns or incidents to the relevant authorities.

Specific Safety Precautions for Use

- Ensure that the mounting surface is clean and free from debris before installation.
- Use appropriate tools as specified in the installation instructions.
- Verify that the ring mount is securely fastened before using the mounted optics.
- Avoid overtightening the mounting screws, as this may damage the product or the mounted optics.
- Be cautious when handling the product, as sharp edges may be present.
- Do not use the product in conditions that exceed its specifications or intended use.

Instructions for Installation and Usage

1. Preparation

- Gather all necessary tools and components.
- Ensure the work area is clean and welllit.

2. Installation Steps

- Position the ring mount on the desired location of the Picatinny rail.
- If using the standard nut configuration:
 - Align the nut with the corresponding hole on the ring mount.
 - Secure the nut using the appropriate tool until snug but not overtightened.
- If using the toolfree, quickdetach (QD) safety lever system:
 - Position the lever over the rail and press down to engage.
 - Ensure the lever is fully engaged and locked in place.

3. Adjustment

- Use the adjustable aluminum safety levers to finetune the tension.
- Ensure a solid lock on the rail by testing the mount's stability.

4. Usage

- After installation, check the alignment of the mounted optics.
- Regularly inspect the mount for signs of wear or looseness during use.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the product in regular household waste.
- Consider recycling options for aluminum components.

Contact Information for Further Support

For any questions or concerns regarding the TwoPiece Ring Mounts ERATAC, please refer to the manufacturer's website or contact your retailer for assistance.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk