

Two-Piece Ring Mounts - ERATAC Ring Mount, 34 mm, H 13mm, nut

Mil-Spec Engineering: Crafted from aircraft-grade, high-strength aluminum and finished with a non-reflective, matte black Mil-Spec Type III hardcoat anodization.



Dual Fastening Options: Choose between a standard nut configuration or a tool-free, quick-detach (QD) safety lever system for rapid mounting and removal.

Adaptable Rail Tension: The adjustable aluminum safety levers can be easily fine-tuned to ensure a rock-solid lock on out-of-spec or non-standard Picatinny rails.

Tactical Modular Interface: Boasting a robust 25 mm ring width, every single ring is equipped with the integrated ERATAC UNIVERSAL interface to support secondary optics and accessories.

Attributes

- Name: ERATAC Ring Mount, 34 mm, H 13mm, nut
- Manufacturer: ERATAC
- Product no.: EU2017957
- Mfr. No.: T5004-0013
- Colour: Black
- Delivery weight: 1kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 100mm
- EAN/UPC: T5004-0013

Table of Contents

- [Startpage](#)
- [English: TwoPiece Ring Mounts ERATAC Ring Mount Safety Instructions](#)

TwoPiece Ring Mounts ERATAC Ring Mount Safety Instructions

Introduction

Thank you for choosing the TwoPiece Ring Mounts ERATAC Ring Mount. This product is designed for safe and reliable use with firearms and optics. Please read this safety instruction guide carefully to ensure proper usage and to minimize risks associated with the product.

General Safety Guidelines

- Ensure that the product is used in accordance with all applicable laws and regulations regarding firearms and accessories in your region.
- Always handle firearms and their accessories with care and respect.
- Inspect the ring mount before each use for any signs of damage or wear.
- Keep the product out of reach of children and vulnerable individuals.
- Report any unsafe products or accidents to the relevant authorities promptly.
- Stay informed about product recalls through the EU's Safety Gate platform.

Specific Safety Precautions for Use

- Before installation, ensure that your firearm is unloaded and pointed in a safe direction.
- Use only compatible optics with the ERATAC Ring Mount to prevent accidents.
- Do not exceed the recommended weight limit for optics mounted on the ring.
- Avoid using the product in extreme environmental conditions that may compromise its integrity.
- Regularly check the mounting screws and levers for tightness and security.
- If using the quickdetach (QD) safety lever system, ensure it is fully engaged before use.

Instructions for Installation and Usage

1. Preparation:

- Gather all necessary tools, including a torque wrench if required.
- Ensure your work area is clean and free from distractions.

2. Installation:

- Locate the Picatinny rail on your firearm where the ring mount will be installed.
- If using the standard nut configuration:
 - Place the ring mount onto the rail and align it with the desired position.
 - Secure the mount using the provided nut and tighten it to the manufacturer's specifications.
- If using the toolfree, quickdetach (QD) safety lever system:
 - Position the ring mount on the rail and press the safety lever down until it clicks into place.
 - Ensure the lever is locked and does not move when tested.

3. Usage:

- After installation, mount the compatible optic onto the ring mount.
- Adjust the aluminum safety levers to ensure a secure fit on the rail.
- Test the stability of the mount by gently applying pressure to the optic.

4. PostUse:

- After use, inspect the ring mount and optics for any signs of wear or damage.
- Clean the mount according to the manufacturer's recommendations.

Disposal Instructions

- Dispose of the product in accordance with local regulations for electronic waste and materials.
- Do not dispose of the product in regular household waste.
- Consider recycling options available in your area to minimize environmental impact.

Contact Information for Further Support

For any inquiries or further support regarding the TwoPiece Ring Mounts ERATAC Ring Mount, please refer to the official manufacturer's website or contact their customer service for assistance.