

Adapters for Universal Interface - Backup Sight with LUMIFIX-fiber optic front sight

Instant Tactical Failsafe: Engineered to attach directly to the integrated UNIVERSAL interface on ERATAC one-piece block or two-piece scope mounts. Traditional backup iron sights sit folded underneath the scope's eyepiece, requiring you to completely remove your primary optic if it fails. The ERATAC interface sight solves this by allowing your riflescope to remain securely mounted on the rifle, ensuring a lightning-fast transition when seconds count. Immediate Close-Range Capability: Beyond acting as an emergency backup, this sight is highly effective for transitioning to unexpected, close-range targets when your primary optic is dialed in for high-magnification, long-distance shots. Battery-Free Reliability: Unlike secondary red dot sights that rely on electronics, this mechanical iron sight requires no batteries—guaranteeing 100% operational readiness at all times, under any weather conditions. Customizable Sight Picture: Available with either a classic, rugged steel post front sight or a high-visibility, light-gathering red fiber-optic front sight. Precision Adjustments: Features a crisp, tactile click adjustment increment of 3 cm at 100 meters (1 MOA). With a generous total tracking range of 240 cm at 100 meters (2.4\text{ m } / \text{ } 100\text{ m}) for both windage and elevation, zeroing your rifle is fast and effortless. Duty-Grade Defense Architecture: Designed with a compact, minimal footprint featuring heavy-duty lateral protective wings to shield the sight post from harsh impacts. Machined exclusively from premium stainless components and finished with a resilient Mil-Spec technical coating for maximum longevity in the field.



Attributes

- Name: Backup Sight with LUMIFIX-fiber optic front sight
- Manufacturer: ERATAC
- Product no.: EU2018027
- Mfr. No.: T0953-0016
- Colour: Black
- Delivery weight: 1kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 100mm
- EAN/UPC: T0953-0016

Table of Contents

- [Startpage](#)
- [English: Safety Instruction Guide for Adapters for Universal Interface Backup Sight with LUMIFIXfiber optic front sight](#)

Safety Instruction Guide for Adapters for Universal Interface Backup Sight with LUMIFIX fiber optic front sight

Introduction

Thank you for choosing the Adapters for Universal Interface Backup Sight with LUMIFIX fiber optic front sight. This guide provides important safety information and instructions to ensure the safe and effective use of your product. Please read this guide carefully before installation and usage.

General Safety Guidelines

- Ensure the product is used only for its intended purpose as described in this guide.
- Always handle the sight with care to avoid damage.
- Keep the product out of reach of children and vulnerable individuals.
- Regularly inspect the sight for any signs of damage or wear before use.
- If any part of the sight is damaged, discontinue use immediately and seek assistance.
- Do not attempt to modify or disassemble the sight, as this may result in hazards or void the warranty.

Specific Safety Precautions for Use

- Always ensure that your firearm is pointed in a safe direction when attaching or detaching the sight.
- Verify that the sight is securely attached to the firearm before use.
- Be aware of your surroundings and ensure that you have a clear line of sight before firing.
- Use appropriate eye protection when using the sight and firearm.
- Avoid using the sight in extreme weather conditions that may affect its performance.
- If you experience any malfunctions or issues with the sight, stop using it and consult a professional.

Instructions for Installation and Usage

1. Installation

- Ensure the firearm is unloaded and pointed in a safe direction.
- Locate the integrated UNIVERSAL interface on your ERATAC scope mount.
- Align the sight with the interface and securely attach it according to the manufacturer's instructions.
- Doublecheck that the sight is firmly mounted and does not wobble.

2. Usage

- Before using the sight, familiarize yourself with its features and adjustments.
- Adjust the sight for windage and elevation using the tactile click adjustment mechanism.
- Transition between your primary optic and the backup sight smoothly by practicing in a safe environment.
- Regularly check the sight for any movement or misalignment during use.

Disposal Instructions

- Dispose of the sight in accordance with local regulations regarding electronic and mechanical waste.
- Do not dispose of the sight in regular household waste.
- If unsure about disposal methods, consult local waste management authorities for guidance.

Contact Information for Further Support

For any safety inquiries or support related to the Adapters for Universal Interface Backup Sight with LUMIFIX fiber optic front sight, please refer to the manufacturer's contact details provided with your product.

Thank you for prioritizing safety while using the Adapters for Universal Interface Backup Sight. Your adherence to these guidelines will help ensure a safe and enjoyable experience.